



How breakthroughs begin.™

Isilon IQ 1920, 3000 & 6000 Specifications



PRODUCT ATTRIBUTES

Clustered Architecture	Truly distributed, fully symmetric clustered architecture that combines modular storage nodes with Isilon's intelligent software.
Modular Design	Self-contained nodes include server, software and disks in a 2U rack-mountable node.
Distributed File System	Isilon® OneFS® operating system software. Creates a cluster with a single file system and single global namespace. Fully journaled, fully distributed globally coherent write/read cache.
High-Availability	No single point of failure. Self-healing design protects against disk or node failures. Includes backend intracluster failover.
Scalability	Initial cluster set-up in under 10 minutes. Add new nodes for performance and capacity in 60 seconds.
Protection Levels	FlexProtect-AP file-level striping with support for N+1, N+2, N+3, N+4 and mirroring data protection schemes.
Network Protocol Support	NFS v3 (UDP or TCP), CIFS, FTP, HTTP reads/writes.
Client Support	Microsoft® Windows , Linux, UNIX, Apple® Macintosh.
Front-End Networking	Two (2) copper 1000 Base-T (Gigabit Ethernet) per node.
Intracluster Networking	Either two (2) InfiniBand® connections or two (2) Gigabit Ethernet connections per node.

SOFTWARE FEATURES

Automatic Content Migration	AutoBalance automatically redistributes data and maximizes utilization across entire cluster when new nodes are added. No downtime, application changes or manual intervention is required.
Accelerated Access to Content	Files are striped across nodes in a cluster. SmartCache algorithms predict content access patterns and accordingly cache data to ensure maximum performance for popular files in a huge and unified memory cache.
Flexible File Protection	FlexProtect-AP allows data protection levels to be changed on the fly and can be set at cluster, directory and file levels. Operates as a background operation, requiring no downtime.
Platform Extension	TrueScale™ enables the addition of Isilon IQ Accelerator and EX 6000/9000 extension products to scale performance and capacity independently.
Management	Powerful web-based management interface. Command line interface (Telnet/SSH). Front panel LCD.
Quotas	SmartQuotas track and report storage utilization at the user, group and directory levels and alert system administrator(s) when users exceed pre-set limits.
Monitoring	Support for SNMP v2/v3. Environmental monitoring system for monitoring fans, power, temperature, operating voltages and node status. Web-based and LCD/LED monitoring of health, capacity and performance.
Alerting	Email alerts to administrator(s). Email-home to Isilon for proactive customer support. Front panel LCD and LEDs. SNMP support.
Authentication and Security	Support for Microsoft Active Directory Services (ADS), Network Information Service (NIS) and Lightweight Directory Access Protocol (LDAP).
Data Integrity	MediaScan proactive file-level health check continuously and automatically runs in the background to analyze and heal files, ensuring long-term data integrity.
Backup and Restore	Supports standard NDMP v3 and v4.

LICENSABLE APPLICATION SOFTWARE

SyncIQ	Delivers extremely fast replication of files across multiple Isilon IQ clusters over WAN and LAN.
SnapshotIQ	Delivers breakthrough snapshot technology for simple, flexible and scalable data protection of large storage environments.
SmartConnect	Maximizes performance and availability of client connections by providing automatic load balancing and NFS failover across all Isilon IQ nodes within the cluster.

Isilon IQ 1920, 3000 & 6000 Specifications

ENVIRONMENTAL SPECIFICATIONS

Power Supply	Dual redundant, hot-swappable 500W power supplies with Power Factor Correction (PFC)
AC Input/Power Consumption	100-240VAC, (60-50 Hz), Typical: 4.5-2A Maximum: 7-3.5A
Thermal Rating	2400 BTU/hr
Operating Environment	50° F to 95° F (10° C to 35° C), 5% to 95% relative humidity, non-condensing
Non-Operating Environment	-40° F to 149° F (-40° C to 65° C), 5% to 95% relative humidity, non-condensing
Dimensions/Weight	Height: 3.48" (8.8 cm), Width: 18.87" (47.9 cm), Depth: 28.5" (72.4 cm), Weight: 65 lbs / 29.5 kg
Minimum Service Clearances	Front: 35" (88.9 cm), Rear: 14" (35.6 cm)

Single Node Attributes	Isilon IQ 1920 / 1920i			Isilon IQ 3000 / 3000i			Isilon IQ 6000 / 6000i		
Capacity	1.92 TB			3.00 TB			6.00 TB		
Hard Drives	Twelve (12) hot-swappable 3.5 SATA-2 160 GB HDD			Twelve (12) hot-swappable 3.5 SATA-2 250 GB HDD			Twelve (12) hot-swappable 3.5 SATA-2 500 GB HDD		
Storage Expansion	N/A			N/A			YES — via Serial Attached SCSI (SAS)		
CPU Type	3.2 GHz Intel Xeon™								
Front-End Networking	Two (2) copper 1000 base-T (Gigabit Ethernet) per node								
Intracuster Networking	Either Two (2) InfiniBand® connections or Two (2) Gigabit Ethernet connections per node								
ECC Memory	4 GB Cache								
Non-volatile RAM (NVRAM)	512 MB								
External Indicators	Cluster status and alert (LED) and front panel LCD								
Cluster Attributes	3 Nodes (min cluster)	10 Nodes	96 Nodes (max cluster)	3 Nodes (min cluster)	10 Nodes	96 Nodes (max cluster)	3 Nodes (min cluster)	10 Nodes	96 Nodes (max cluster)
Capacity (TB)	5.7	19.0	184	9	30	288	18	60	576
Memory (GB)	12	40	384	12	40	384	12	40	384
Rack Units (RU)	6U	20U	176U	6U	20U	176U	6U	20U	176U

INDUSTRY CERTIFICATIONS

North American (NA) Safety

UL/cUL Listing (UL 60950-1:2003, First Edition)
CSA C22.2 No.60950-1-03

International Safety

CB Scheme IEC 60950-1 (2001) First Edition with all national deviations

European Union (EU) Safety

CE, Low Voltage Directive

NA EMC

US FCC Part 15/ Canada IC ICES-03

International EMC

EU EMC Directive (EN 55022 & EN 55024)
Japan (VCCI) South Korea (MIC)

Isilon Systems, Inc. | www.isilon.com
3101 Western Ave, Seattle, WA 98121

Toll-Free: 877-2-ISILON • **Phone:** +1-206-315-7602
Fax: +1-206-315-7501 • **Email:** sales@isilon.com

