

- [Home](#)
- [Products](#)
- [Support](#)
 - [Search the Knowledge Base](#)
 - [Ask APC](#)
 - [My Support](#)
- [Services](#)
- [Selectors](#)
 - [UPS Selector](#)
 - [InfraStruXure Estimator](#)
 - [Wiring Closet And Server Room Selector](#)
 - [UPS Upgrade Selector](#)
 - [Surge Protection Selector](#)
 - [Rack Configurator](#)
 - [Service Selector](#)
- [How to Buy](#)
 - [Try out the APC Product Selectors](#)
 - [Online Reseller Listing](#)
 - [Locate a Reseller/Partner](#)

[Home](#) >> [Products](#) >> [Power Distribution](#) >> [Basic Rack PDU](#)

Basic Rack PDU

Rack PDU, Basic, Zero U, 20A, 120V, (24)5-20



APC Basic Rack PDU , Input: 100V, 120V , Input Connections: NEMA L5-20P , Cord Length: 10 feet (3.05 meters) , Output: 120V , Output Connections: NEMA 5-20R

Includes: Cord retention bracket(s), Installation guide, Rack Mounting brackets, Toolless Mounting Kit, User Manual

AP7530

 [Email Technical Specifications](#)

 [Printer Friendly](#)




[+ More Images](#)


Standard Lead Time: Usually in Stock

- [Technical Specifications](#)
- [Product Overview](#)
- [Documentation](#)
- [Options](#)
- [Compare Models](#)

Output

Nominal Output Voltage	120V	
Maximum Total Current Draw per Phase	16A	
Output Connections	(24) NEMA 5-20R	
Always on Outlets	24	
Overload Protection	No	

Input

Nominal Input Voltage	100V,120V	
Input Frequency	50/60 Hz	
Regulatory Derated Input Current (North America)	16A	
Input Connections	NEMA L5-20P	
Cord Length	3.05 meters	
Number of Power Cords	1	
Acceptable Input Voltage	100-120 VAC	
Maximum Input Current per phase	20A	
Load Capacity	1920 VA	

Physical

Net Weight	4.86 KG
Maximum Height	1619.00 mm
Maximum Width	56.00 mm
Maximum Depth	44.00 mm
Shipping Weight	5.77 KG

Shipping Height	2134.00 mm
Shipping Width	152.00 mm
Shipping Depth	127.00 mm
Color	Black

Environmental

Operating Environment	-5 - 45 °C
Operating Relative Humidity	5 - 95%
Operating Elevation	0-4500 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	cUL Listed,CSA C22.2 No. 60950-1-03,UL 60950-1,UL Listed
Standard Warranty	2 years repair or replace
Environmental Compliance	RoHS 7b Exemption