

- [Home](#)
- [Products](#)
- [Support](#)
  - [Search the Knowledge Base](#)
  - [Ask APC](#)
  - [My Support](#)
- [Services](#)
- [Selectors](#)
  - [UPS Selector](#)
  - [InfraStruXure Estimator](#)
  - [Wiring Closet And Server Room Selector](#)
  - [UPS Upgrade Selector](#)
  - [Surge Protection Selector](#)
  - [Rack Configurator](#)
  - [Service Selector](#)
- [How to Buy](#)
  - [Try out the APC Product Selectors](#)
  - [Online Reseller Listing](#)
  - [Locate a Reseller/Partner](#)

[Home](#) >> [Products](#) >> [Power Distribution](#) >> [Switched Rack PDU](#)

## [Switched Rack PDU](#)

### **Rack PDU, Switched, 1U, 16A, 208/230V, (8)C13**



APC Switched Rack PDU , Input: 200V, 208V, 230V , Input Connections: IEC-320 C20 , Cord Length: 8.2 feet ( 2.5 meters ) , Output: 208V, 230V , Output Connections: IEC 320 C13

**Includes:** Installation guide, Rack Mounting brackets, User Manual

**Standard Lead Time:** Usually in Stock

AP7921

 [Email Technical Specifications](#)


 [Printer Friendly](#)



[+ More Images](#)

- [Technical Specifications](#)
- [Product Overview](#)
- [Documentation](#)
- [Software & Firmware](#)
- [Options](#)
- [Compare Models](#)

**Output**

Nominal Output Voltage	208V,230V	
Maximum Total Current Draw per Phase	16A	
Output Connections	(8) IEC 320 C13	

**Input**

Nominal Input Voltage	200V,208V,230V
Input Frequency	50/60 Hz
Regulatory Derated Input Current (North America)	16A
Input Connections	IEC-320 C20
Cord Length	2.5 meters
Number of Power Cords	1
Acceptable Input Voltage	200-240 VAC
Maximum Input Current per phase	20A
Load Capacity	3680 VA

**Physical**

Net Weight	2.27 KG
Maximum Height	44.00 mm
Maximum Width	445.00 mm
Maximum Depth	108.00 mm
Shipping Weight	3.45 KG
Shipping Height	70.00 mm
Shipping Width	470.00 mm

Shipping Depth	343.00 mm
Color	Black

#### Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

#### Conformance

Regulatory Approvals	cUL Listed,CE,CSA,EN 55022 Class A,EN 55024,EN 61000-3-2,EN 61000-3-3,GOST,IRAM,MIC,UL 60950,UL Listed,VDE,VCCI
Standard Warranty	2 years repair or replace
Environmental Compliance	RoHS 7b Exemption,China RoHS,REACH: Contains No SVHCs

[Copyright](#) © American Power Conversion Corp., all rights reserved