

# B-Series B2

## Fast Ethernet Stackable L2/L3/L4 Edge Switch with Optional Policy Support



High-availability design assures reliable network operations

Granular QoS capabilities support converged multimedia networks

Aligns network resource utilization with business goals and priorities

PoE supports a variety of network devices

Investment protection via lifetime warranty

460 Gbps capacity and 104 Mpps

### Product Overview

The Enterasys B2 is a high-performance, Fast Ethernet edge switch that provides scalable, wire-rate performance in support of the bandwidth-intensive and delay-sensitive requirements of today's demanding applications. With support for 16,000 MAC addresses, the B2 is an excellent choice for environments that require complete multi-layer switching capabilities and support for high density 10/100 Ethernet ports. The B2 is well-suited for 100 Mbps networks that may migrate to a predominantly Gigabit Ethernet network. In addition to its complete multi-layer switching capabilities, the B2 also provides multi-layer packet classification and priority queuing for differentiated services. Along with a switch capacity of 57.6 Gbps, the B2 provides up to 48 10/100 Ethernet ports as well as 4 Gigabit Ethernet uplink ports. Leveraging the B2's wire-rate stacking capability, as many as 8 B2s can be interconnected in a single stack to create a virtual switch that provides 460.8 Gbps of capacity and up to 384 10/100 Ethernet ports as well as 32 Gigabit Ethernet uplink ports.

Robust Quality of Service (QoS) features enable strong support for integrated multimedia networks, including Voice over IP (VoIP) and video, as well as all types of data-intensive applications. The B2's optional policy license enables its highly customizable Layer 2/3/4 packet classification capabilities to work together with the 8 hardware-based priority queues associated with each Ethernet port to support a suite of differentiated services with as many as 8 distinct priority levels. In conjunction with its non-blocking L2 switching architecture, the B2's intelligent queuing mechanisms ensure that mission-critical applications receive prioritized access to network resources.

The B2 provides a secure network by utilizing its authentication and security features, which can be applied at the port level or at the user level. Making use of the NMS Policy Manager or a standard CLI, the Enterasys role-based architecture enables a network administrator to define distinct roles or profiles that represent operational groups within a business (e.g., employee, executive, guest, etc). Multiple users/devices per switch can be authenticated via IEEE 802.1X, MAC address, or web authentication, and then assigned a pre-defined operational role. Network operations can be easily tailored to meet business-oriented requirements by providing each role with individualized access to network services and applications (e.g., a guest should have different network access privileges than an employee).

## Benefits

### Business Alignment

- Granular QoS capabilities support converged multimedia networks
- Aligns network resource utilization with business goals and priorities
- Reliable network operation for mission-critical applications

### Operational Efficiency

- Scalable architecture supports continued growth of network capacity
- Consolidated management capabilities reduce network operational expenses
- Security capabilities without the high overhead

### Security

- Network resources securely allocated according to user roles
- Network security maintained concurrently with user mobility
- Architecture designed with integral network security

### Support and Service

- Industry-leading customer satisfaction and first call resolution rates
- Personalized services, including site surveys, network design, installation, and training
- Lifetime warranty

**There is nothing more important  
than our customers.**

---

The B-Series product line provides high port density in a 1u footprint and is environmentally friendly by design. By maximizing port density within a given amount of rack space, the B2 minimizes its cooling requirements. The B2's overall electrical requirement is further reduced by a low current draw and an extreme tolerance for high environmental temperatures. A highly-scalable architecture and a lifetime warranty ensures that an B2 network investment will sustain a secure, feature-rich and cost-effective network well into the future.

## Reliability and Availability

The B2 design incorporates redundancy and failure protection mechanisms complete with automatic failover and recovery capabilities to provide a reliable network. An integral power supply is the primary source of power for the B2 and complete power redundancy is provided by an optional external power supply. In addition to the standard version of the B2, there is also a redundant Power over Ethernet (PoE) version of the B2 which supports network devices that require external power such as wireless access points, VoIP phones, and network cameras. A virtual switch can be created by interconnecting as many as 8 B2s in a single stack, which can be managed via a single IP address with redundant management connections. The B2's closed-loop stacking (CLS) capability utilizes bidirectional switch interconnects to maintain connectivity within the virtual switch despite any physical switch-level failure. Up to 8 Ethernet ports can be grouped together to create a multi-link aggregation group (LAG). A LAG's Ethernet ports can be collocated on a single B2 or they can be distributed across multiple B2s within a stack to prevent a switch-level failure from disrupting data communications.

## Advanced Quality of Service

Robust QoS features enable strong support for integrated multimedia networks, including VoIP and video, as well as all types of data-intensive applications. With an optional policy license, the B2 provides highly customizable Layer 2/3/4 packet classification capabilities, which can be based upon physical port ID, MAC address, IP subnet, IP address, IP protocol type, IP Type of Service (ToS), differentiated services code point (DSCP), and TCP/UDP port. The B2 provides 8 hardware-based priority queues per Ethernet port, which work together with its packet classification capabilities to support a suite of differentiated services with as many as 8 distinct priority levels. The strict and weighted round robin queuing algorithms ensure that mission-critical applications receive prioritized access to network resources.

## Security

The B2 provides a secure network by utilizing its authentication and security features, which can be applied at the port level or at the user level. Making use of the NMS Policy Manager or a standard CLI, the Enterasys role-based architecture enables a network administrator to define distinct roles or profiles that represent operational groups within a business (e.g., employee, executive, guest, etc). Multiple users/devices per switch can be authenticated via IEEE 802.1X, MAC address, or web authentication, and then assigned a pre-defined operational role. Network operations can be easily tailored to meet business-oriented requirements by providing each role with individualized access to network services and applications (e.g., a guest should have different network access privileges than an employee).

## Investment Protection

The B2 is a cost-effective, feature-rich, stackable switch that provides a broad set of features today and will continue to deliver benefits well into the future. Customers can grow and/or enhance their networks while protecting their investment by adding B2s into existing B-Series networks and/or stacks. When multiple B2s are stacked together, each switch in the stack assumes the feature set that is common to all switches in the stack to ensure operational compatibility. All B-Series products include a lifetime warranty that continues for 5 years after the date of product discontinuation. For more information regarding warranty terms and conditions please go to <http://www.enterasys.com/support/warranty.aspx>.

## Performance & Scalability

The B2 provides scalable, wire-rate performance in support of the bandwidth-intensive and delay-sensitive requirements of today's demanding applications. Along with a switch capacity of 57.6 Gbps, the B2 provides up to 48 10/100 Ethernet ports as well as 4 Gigabit Ethernet uplink ports. Leveraging the B2's wire-rate stacking capability, as many as 8 B2s can be interconnected in a single stack to create a virtual switch that provides 460.8 Gbps of capacity and up to 384 10/100 Ethernet ports as well as 32 Gigabit Ethernet uplink ports. The B2 supports hundreds of distinct policies (rules) that enable granular definition of network access capabilities for each role, thus aligning network resource utilization with business goals and priorities.

# Standards and Protocols

## MAC Address Table Size

16,000

## VLANs

4,096 VLAN IDs

1,024 VLAN Entries per Stack

## Embedded Services

Ingress Rate Limiting

IP TOS Rewrite

Layer 2/3/4 Classification

Multi-layer Packet Processing

## Switching Services

IEEE 802.1D – MAC Bridges

IEEE 802.1s – Multiple Spanning Trees

IEEE 802.1t – 802.1D Maintenance

IEEE 802.1w – Rapid Spanning Tree

Reconvergence

IEEE 802.3 - Ethernet

IEEE 802.3ab – GE over

Twisted Pair

IEEE 802.3ad – Link Aggregation

IEEE 802.3af – PoE

IEEE 802.3i – 10Base-T

IEEE 802.3u – 100Base-T, 100Base-FX

IEEE 802.3z – GE over Fiber

Full/half duplex auto-sense support on all ports

IGMP Snooping v1/v2/v3

Jumbo Frame support (9,216 bytes)

Loop Protection

One-to-One and Many-to-One Port Mirroring

Port Description

Protected Ports

Per-port Broadcast/Multicast/Unknown

Unicast Suppression

Spanning Tree Backup Root

STP Pass Thru

## VLAN Support

Generic Attribute Registration Protocol (GARP)

Generic VLAN Registration Protocol (GVRP)

IEEE 802.1p – Traffic Management/Mapping to 8 Queues

IEEE 802.1q – VLAN Tagging

IEEE 802.1v – Protocol-based VLANs

IEEE 802.3ac – VLAN Tagging Extensions

Protected Port (private port/private VLAN)

Tagged-based VLAN

VLAN Marking of Mirror Traffic

## Quality of Service

8 Priority Queues per Port

802.3x Flow Control

IP DSCP – Differentiated Services Code Point

IP Precedence

IP Protocol

Queuing Control – Strict and Weighted

Round Robin

Source/Destination IP Address

Source/Destination MAC Address

## Security

ARP Spoof Protection

DHCP Spoof Protection

Dynamic and Static MAC Locking

EAP Pass Thru

IEEE 802.1x Port Authentication

MAC-based Port Authentication

RADIUS Accounting for MAC Authentication

RADIUS Client

RFC 3580 – Dynamic VLAN Assignment

Password Protection (encryption)

Secure Networks Policy License

Secured Shell (SSHv2)

Secured Socket Layer (SSL)

User and IP Phone Authentication

Web-based Port Authentication

## RFC and MIB Support

Enterasys Entity MIB

Enterasys Policy MIB

Enterasys VLAN Authorization MIB

IEEE 802.1X MIB – Port Access

IEEE 802.3ad MIB – LAG MIB

RFC 826 – ARP and ARP Redirect

RFC 1213 – MIB/MIB II

RFC 1493 – BRIDGE-MIB

RFC 1643 – Ethernet-like MIB

RFC 2131 – DHCP

RFC 2271 – SNMP Framework MIB

RFC 2618 – RADIUS Authentication

Client MIB

RFC 2620 – RADIUS Accounting Client MIB

RFC 2668 – Managed Object Definitions for 802.3 MAUs

RFC 2674 – P-BRIDGE-MIB

RFC 2674 – QBRIDGE-MIB VLAN Bridge MIB

RFC 2737 – Entity MIB (physical branch only)

RFC 2819 – RMON-MIB

RFC 2863 – IF-MIB

RFC 2933 – IGMP MIB

RFC 3289 – DiffServ MIB

RFC 3413 – SNMP Applications MIB

RFC 3414 – SNMP User-based Security

Module (USM) MIB

RFC 3415 – View-based Access Control Model for SNMP

RFC 3580 – IEEE 802.1X Remote

Authentication Dial-in User Service (RADIUS)

Usage Guidelines

RFC 3584 – SNMP Community MIB

RFC 3621 – Power over Ethernet MIB

## Management

Alias Port Naming

Command Line Interface

Editable Configuration File

TFTP client

Multi-configuration File Support

NMS Automated Security Manager

NMS Console

NMS Inventory Manager

NMS Policy Manager

Node/Alias Table

RFC 854 – Telnet

RFC 1157 – SNMP

RFC 1901 – Community-based SNMPv2

RFC 2271 – SNMP Framework MIB

RFC 3413 – SNMP Applications MIB

RFC 3414 – SNMP Usr MIB

RFC 3415 – View-based Access Control Model for SNMP

RMON (Stats, History, Alarms, Events)

Simple Network Management Protocol (SNMP) v1/v2c/v3

Simple Network Time Protocol (SNTP)

SSH

Syslog

Text-based Configuration Upload/Download

Web-based Management

Webview via SSL Interface

# Switch Model Specifications

	B2H124-48	B2H124-48P
<b>Performance</b>		
Throughput Capacity wire-speed Mpps (switch / stack)	13.1 Mpps / 104.8 Mpps	13.1 Mpps / 104.8 Mpps
Switching Capacity (switch / stack)	17.6 Gbps / 140.8 Gbps	17.6 Gbps / 140.8 Gbps
Stacking Capacity (switch / stack)	40 Gbps / 320 Gbps	40 Gbps / 320 Gbps
Aggregate Throughput Capacity (switch / stack)	57.6 Gbps / 460.8 Gbps	57.6 Gbps / 460.8 Gbps
<b>PoE Specifications</b>		
802.3af Compliance	N/A	Yes
System Power	N/A	360 watts per switch with up to 15.4 watts per port  Per-port switch power monitor: <ul style="list-style-type: none"> <li>• Enable/disable</li> <li>• Priority safety</li> <li>• Overload &amp; short circuit protection</li> </ul>
<b>Physical Specifications</b>		
Dimensions (H x W x D)	H: 4.4 cm (1.73") W: 44.1 cm (17.36") D: 36.85 cm (14.51")	H: 4.4 cm (1.73") W: 44.1 cm (17.36") D: 36.85 cm (14.51")
Net Weight	5.27 kg (11.61 lb)	6.50 kg (14.32 lb)
MTBF	138,741 hours	115,872 hours
Physical Ports	<ul style="list-style-type: none"> <li>• (48) 10/100 auto-sensing, auto-negotiating, MDI/MDI-X RJ45 ports</li> <li>• (4) mini-GBIC ports</li> <li>• (2) dedicated stacking ports</li> <li>• (1) DB9 console port</li> <li>• (1) RPS port</li> </ul>	<ul style="list-style-type: none"> <li>• (48) 10/100 PoE auto-sensing, auto-negotiating, MDI/MDI-X RJ45 ports</li> <li>• (4) mini-GBIC ports</li> <li>• (2) dedicated stacking ports</li> <li>• (1) DB9 console port</li> <li>• (1) RPS port</li> </ul>
<b>Power Requirements</b>		
Nominal Input Voltage	100 – 240 VAC	100 – 240 VAC
Input Frequency	50 – 60 Hz	50 – 60 Hz
Input Current	0.8 A Max	7.5 A Max
Power Consumption	79 watts	535 watts
<b>Temperature</b>		
IEC 6-2-1 Standard Operating Temperature	0° to 50° C (32° to 122° F)	0° to 50° C (32° to 122° F)
IEC 6-2-14 Non-Operating Temperature	-40° to 70° C (-40° to 158° F)	-40° to 70° C (-40° to 158° F)
Heat Dissipation	270 BTUs/Hr	384 BTUs/Hr
<b>Humidity</b>		
Operating Humidity	5% - 95% non-condensing	5% - 95% non-condensing
<b>Vibration</b>		
	IEC 68-2-6, IEC68-2-36	IEC 68-2-6, IEC68-2-36
<b>Shock</b>		
	IEC 68-2-29	IEC 68-2-29
<b>Drop</b>		
	IEC 68-2-32	IEC 68-2-32
<b>Agency and Regulatory Standard Specifications</b>		
Safety	UL 60950-1, CSA 22.1 60950, EN 60950-1, and IEC 60950-1	UL 60950-1, CSA 22.1 60950, EN 60950-1, and IEC 60950-1
EMC	FCC Part 15 (Class A), ICES-003 (Class A), BSMI, VCCI V-3, AS/NZS CISPR 22 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, and EN 61000-3-3	FCC Part 15 (Class A), ICES-003 (Class A), BSMI, VCCI V-3, AS/NZS CISPR 22 (Class A), EN 55022 (Class A), EN 55024, EN 61000-3-2, and EN 61000-3-3

# Redundant Power Supply Equipment Specifications

## STK-RPS-150CH2 Power Shelf

### Power Supply Slots

2

### Dimensions (H x W x D)\*

5.5 cm (2.2") x 44.0 cm (17.3") x 18.0 cm (7.0")

### Weight

0.95 kg (2.09 lbs)

*Note: dimensions include integrated rack mount ears*

## STK-RPS-150CH8 Power Shelf

### Power Supply Slots

8

### Dimensions (H x W x D)\*

22.26 cm (8.77") x 44.0 cm (17.3") x 26.4 cm (10.4")

### Weight

5.27 kg (11.6 lbs)

## C2RPS-PSM Power Supply

### Dimensions (H x W x D)

19.6 cm (7.7") x 5.2 cm (2.04") x 25.7 cm (10.1")

### Net Weight (Unit Only)

1.75 kg (3.85 lbs)

### Gross Weight (Packaged Unit)

3.20 kg (7.04 lbs)

### MTBF

300,000 hours

### Operating Temperature

0° C to 50° C (32° F to 122° F)

### Storage Temperature

-30° C to 73° C (-22° F to 164° F)

### Operating Relative Humidity

10% to 90%

### AC Input Frequency Range

50-60 Hz

### AC Input Voltage Range

100 - 240 VAC

### Maximum Output Power

156 W continuous

## C2RPS-POE Power Supply

### Dimensions (H x W x D)\*

4.45 cm (1.75") x 44.5 cm (17.5") x 16.5 cm (6.5")

### Net Weight (Unit Only)

3.47 kg (7.63 lbs)

### Gross Weight (Packaged Unit)

4.95 kg (10.89 lbs)

### MTBF

589,644 hours at 25° C (77° F)

### Operating Temperature

5° C to 40° C (41° F to 104° F)

### Storage Temperature

-30° C to 73° C (-22° F to 164° F)

### Operating Relative Humidity

10% to 90%

### AC Input Frequency Range

50-60 Hz

### AC Input Voltage Range

100 - 240 VAC

### Maximum Output Power

500 W continuous

## Ordering Information

B2 Switches	
Part Number	Description
B2H124-48	B2 with (48) 10/100 RJ45 ports, (4) mini-GBIC ports, and (2) dedicated stacking ports. Total active ports per switch: all 52 ports.
B2H124-48P	B2 with (48) 10/100 PoE RJ45 ports, (4) mini-GBIC ports, and (2) dedicated stacking ports. Total active ports per switch: all 52 ports.
Optional Software Licenses	
B2POL-LIC	B2 policy license (per switch)
B2POL-LIC25	B2 policy licenses – Qty of 25
B2POL-LIC50	B2 policy licenses – Qty of 50
Cables	
C2CAB-SHORT	Stacking cable for connecting adjacent switches (30 cm)
C2CAB-LONG	Stacking cable for connecting top switch to bottom switch (1 m)
SSCON-CAB	Spare Console Cable (for use on all A2, B2, B3, C2, and C3 switches)
Redundant Power Supply Equipment	
STK-RPS-150CH2	2-slot RPS chassis (supports up to 2 C2RPS-PSMs)
STK-RPS-150CH8	8-slot RPS chassis (supports up to 8 C2RPS-PSMs)
C2RPS-PSM	150-watt redundant Non-PoE power supply with one DC cable
C2RPS-SYS	8-slot RPS chassis plus 1 C2RPS-PSM (chassis supports up to 8 C2RPS-PSMs)
C2RPS-POE	500-watt redundant PoE power supply with one DC cable

### Transceivers

Enterasys transceivers provide connectivity options for Ethernet over twisted pair copper and fiber optic cables with transmission speeds from 100 Megabits per second to 10 Gigabits per second. All Enterasys transceivers meet the highest quality for extended life cycle and the best possible return on investment. For detailed specifications, compatibility and ordering information please go to: <http://www.enterasys.com/products/transceivers-ds.pdf>

## Warranty

As a customer-centric company, Enterasys is committed to providing quality products and solutions. In the event that one of our products fails due to a defect, we have developed a comprehensive warranty that protects you and provides a simple way to get your products repaired or media replaced as soon as possible.

B-Series switches come with a lifetime warranty against manufacturing defects. For full warranty terms and conditions please go to: <http://www.enterasys.com/support/warranty.aspx>.

## Service and Support

Enterasys Networks provides comprehensive service offerings that range from Professional Services to design, deploy and optimize customer networks, customized technical training, to service and support tailored to individual customer needs. Please contact your Enterasys account executive for more information about Enterasys Service and Support.

## Contact Us

For more information, call Enterasys Networks toll free at **1-877-801-7082**, or +1-978-684-1000 and visit us on the Web at [enterasys.com](http://enterasys.com)



© 2010 Enterasys Networks, Inc. All rights reserved. Enterasys Networks reserves the right to change specifications without notice. Please contact your representative to confirm current specifications. Please visit <http://www.enterasys.com/company/trademarks.aspx> for trademark information.

