

Summit® 300 Series Switches



Summit 300 series 10/100 Ethernet switches deliver secure Unified Access for IP Telephony and wireless applications.

Voice-Class Availability at the Edge of the Network

- Layer 2 and Layer 3 ESRP for dual-homed configuration
- Redundant gigabit uplink ports for greater throughput and resiliency
- Ethernet Automatic Protection Switching (EAPS) resiliency protocol for sub-second failover

High-Performance with Quality of Service (QoS) for Converged Applications

- Non-blocking architecture with QoS enabling traffic prioritization for delay sensitive applications like IP Telephony and wireless
- IEEE 802.3af Power over Ethernet (PoE) support on all ports
- Wire-speed ACLs for diverse traffic classification

Layer 3 Intelligence and Comprehensive Security at the Edge of the Network

- Access Adapt™ capability and rogue Access Point (AP) detection to securely deploy devices like wireless APs
- Layers 2 – 4 Access Control Lists (ACLs), web-based Network Login, 802.1x, SSH2, TACACS, RADIUS, Denial of Service (DoS) protection, MAC address security
- Routing features for maximum forwarding control at the edge

Summit 300 series switches set the standard for edge connectivity in today's demanding converged network.

With its implementation of Extreme Networks® Unified Access Architecture™ (UAA), Summit 300 series switches set a standard for edge connectivity in today's most demanding converged networks. In addition to offering a solid foundation of performance, security, availability, and management capabilities, Summit 300 series switches provide up to 48 universal access ports, with every port enabling high-performance data to the desktop, PoE, and wireless LAN. With its integrated PoE, the Summit 300 series switches can power devices such as Voice-over-IP (VoIP) phones, surveillance cameras, and badge readers. Because of Extreme Networks' unique UAA, wireless APs can be seamlessly and securely deployed and managed throughout a facility for any number of wireless data or voice applications.

Based on the award-winning ExtremeWare® Layer 3 software, the Summit 300 series switches provide 24 or 48 ports of 10/100 Ethernet with four physical Gigabit Ethernet uplinks. Every port delivers a vast array of ExtremeWare Layer 3 and Layer 2 features; ranging from OSPF routing and advanced QoS classification to the latest advancements in security. Years of development based on the requirements of thousands of customers enables ExtremeWare to deliver the most comprehensive Layer 3 advanced software solution set at the edge while allowing easy expansion and addition of services without major upgrades.

Target Applications

- Unified Access connectivity for integrated wired, wireless and IP Telephony deployments
- Edge security to protect networks where they are being attacked
- Network edge deployments with Layer 3 intelligence and routing to increase efficiency of sub-network edge traffic



Benefits

Summit 300 Series Benefits

High-Performance

Non-blocking wire-speed architecture helps ensure performance for demanding wired and wireless applications. Extreme Networks Altitude APs support 802.11 a, b, and g, today's fastest wireless LAN (WLAN) standards.

Extraordinary Availability

Redundant copper and fiber gigabit uplinks, dual-homed configurations, and sub-second EAPS failover provide mission-critical resiliency. The switch continuously monitors "heartbeats" generated by the Altitude APs, helping to ensure more continuous wireless user operation.

Industry-leading Security

UAA from Extreme Networks provides a single wired/wireless authentication infrastructure for consistent, policy-based security from the edge to the core. Wireless security includes hardware-accelerated AES and RC4 encryption. Extreme Networks also offers rogue AP detection for defending the wireless perimeter of a network.

Scalability

Summit 300 series switches provide PoE to every port for voice, video, data or wireless devices.

End-to-End Manageability

As a member of Extreme Networks' comprehensive family of switches, Summit 300 series switches can be centrally deployed, managed, and monitored using EPICenter® management platform from Extreme Networks or any SNMP-based products. In addition, Extreme Networks offers the RF Manager site survey tool for simplified wireless design and its AccessAdapt™ utility for a no-configuration installation of the Altitude APs.

High-Performance with QoS for Converged Applications

With its non-blocking architecture, Summit 300 series switches enable all RJ-45 copper 10/100 ports to operate at line-rate. Four hardware queues per 10/100 port provide granularity, low latency and low jitter for time-sensitive voice and multi-media applications. These applications also benefit from features such as DiffServ and 802.1p

which deliver varied levels of service and ensure efficient bandwidth usage. Copper and SFP GBIC Gigabit Ethernet uplink ports can be configured as active and redundant for fast Layer 1 failover. These uplink ports provide the added flexibility of port redundancy between copper and fiber ports, enabling backup links to the active uplinks with sub-second (50ms) failover capability through EAPS.

Summit 300 series switches offer a number of features that improve the performance of the network, such as RIP, OSPF, Network Address Translation, QoS classification, dynamic VLANs, and ACLs. For converged applications involving voice or rich media, the switch provides multicast, re-writing 802.1p tag prioritization, or prioritization using Layer 2/3/4. Rate shaping can be used for optimum VoIP performance.

Summit 300 series switches deliver advanced high availability features traditionally reserved for carrier networks. EAPS (RFC 3619) delivers sub-second (less than 50ms recovery) protection switching to interconnected switches in an Ethernet ring topology. Similar to the Spanning Tree Protocol (STP), EAPS offers the advantage of converging in significantly less time than STP or even Rapid Spanning Tree (802.1w) when a link breaks in the ring. Extreme Standby Routing Protocol™ (ESRP) can be implemented at both Layers 2 and 3 and extends the Virtual Redundant Redundancy Protocol's (VRRP) capabilities, adding Layer 2 resiliency and loop prevention and Layer 3 default router redundancy. It can be used as a STP substitute and can be scaled to protect thousands of VLANs. Multiple instances of ESRP in the same VLAN allow direct host attachment to standby switches.

Equal Cost Multipath adds network resiliency as multiple equal-cost routes can be used concurrently to an end destination. With the software redundant port feature, a specified primary port can be backed up by another port. Should the link go down on the primary port, the redundant port will establish a link and become active. Thus multi-homed redundancy can be easily designed without the implementing complexity of a protocol.

For PoE, the switch generates up to 15.4 watts of PoE for devices such as VoIP phones, surveillance cameras, badge readers, Extreme Networks Altitude APs and "fat" APs sold by other vendors. When used with Altitude APs, Summit 300 series switches provide wireless performance as each AP simultaneously broadcasts both 802.11a and 802.11b/g. Extreme Networks has also implemented the SpectraLink Voice Protocol, a QoS standard used by the leading WLAN handsets today for recognizing and prioritizing voice packets. When enabled in tandem with the Inter-Access Point Protocol which allows Layer 2 roaming between APs, Voice over Wireless LAN (VoWLAN) users can productively communicate with customers, patients, emergency personnel and employees anytime within a facility.



The Summit 300 series switches enable high quality VoWLAN with leading handsets such as SpectraLink.

Compared to other vendors' point solutions, Summit 300 series switches offer a low Total Cost of Ownership because they are fully integrated into Extreme Networks family of edge, aggregation, and core end-to-end solutions. ExtremeWare Layer 2 and Layer 3 features implemented in Summit 300 series switches are shared with all other Extreme Networks platforms in the Summit product line as well as with Alpine® and BlackDiamond® switches.

From a PoE/wireless perspective, Summit 300 series switches are complementary to the BlackDiamond 8800 series PoE blade, and the Alpine 3800 PoE blade. Each of these switches supports UAA, providing a seamless infrastructure for voice and data support on both wired and wireless networks. EPICenter management platform makes it easy to develop centralized configuration and management policies throughout the network. Summit 300 series switches also uses the same Command Line Interface (CLI) and the same management commands as other Extreme switches so training time and expense are reduced as operational expertise can be shared over an entire network solution.

Layer 3 Intelligence and Comprehensive Security at the Edge of the Network

Enterprise networks need both Layer 2 and Layer 3 intelligent services at the edge to ensure maximum network efficiency. Intelligence supports critical functionality such as security to prevent unauthorized access, high availability to ensure network uptime, and common management to reduce expenses.

Security is a paramount concern in today's converged networks. UAA provides consistent wired and wireless security from the edge to the core. ExtremeWare supports multiple authentication options including 802.1x, web-based login with Secure Sockets Layer (SSL), and MAC address. With IEEE 802.1x login, network managers can always control who is accessing and connected to the network. Web-based Network Login offers the freedom of authenticating through any HTTP-compliant web browser. During the authentication process, SSL encrypts logon information.

MAC Address Security prevents unauthorized port abuse from rogue wireless APs or hubs/switches on edge ports. Port abuse can be reduced using lockdown on a per port basis and/or limiting of the number of MAC addresses learned by a port. The lockdown feature and saving learned MAC addresses between reboots can be used, for example, to help protect dedicated ports for VoIP phones or printers from abuse. Limiting the number of MAC addresses learned on a port also allows enforcement of service level agreements in tenant or service provider environments. MAC Address Security can also be used in conjunction with a RADIUS server to allow devices such as bar code readers that do not support 802.1x to enter the network based on their MAC address.

Multiple Supplicant (client) enables clients to be individually authenticated on the same port. This ensures that all clients are authenticated to a wireless AP or hub. Without this, a client could authenticate, leaving the port open for additional clients to connect without authentication. Wire-speed Layers 2 – 4 ACLs provide port security without worrying about the degrading performance and disrupting business applications or reducing productivity. SSHv2 allows network managers to securely and remotely configure the switch with less risk of packet snooping or man-in-the-middle attacks.

SSHv2, Denial of Service (DoS) protection, TACACS+ and RADIUS provide reliable and more secure configuration traffic (encryption) and authentication.

As part of its UAA, Extreme Networks has comprehensively designed for wireless security. The Altitude AP offers scalable, hardware-accelerated AES and RC4 encryption. Extreme Networks also offers rogue AP detection for defending the wireless perimeter of a network. Perimeter defense is monitored and reported by EPICenter, which also offers a “one-click” command to disable the rogues. Optional directional antennas can be used to focus the wireless beam into the enterprise's facility. And finally, the Altitude is a “thin” AP, reducing the physical theft of critical security parameters because it loses its configuration as soon as it is unplugged.

Summit 300 Series Feature Set Summary

Hardware Features

Summit 300-48

- 48 10/100 auto-negotiating Ethernet ports in a 2RU footprint
- 4 10/100/1000BASE-T copper ports and 4 SFP GBIC ports deliver four active gigabit uplinks for greater throughput and four redundant uplinks for high availability
- Power supply provides 450W of available power for PoE devices. Each port supports IEEE 802.3af Class 3 (15.4W) devices. An optional hot-swappable power supply (p/n 15412) provides 30 additional watts of power—for a total of 480 watts of PoE—as well as redundancy for transparent failover.

Summit 300-24

- 24 10/100 auto-negotiating Ethernet ports in a 1RU footprint allow more network connections per inch of rack space
- 2 10/100/1000BASE-T copper ports and 2 mini-GBIC ports deliver two active gigabit uplinks for greater throughput and two redundant uplinks for high availability
- Single AC power supply. Provides 370W of available power for PoE devices, supporting up to 24 IEEE 802.3af Class 3 (15.4W) devices. External redundant power supply available optionally.

Performance Features

Summit 300-48

- Non-blocking wire-speed architecture
- 32 Gbps switching fabric, enabling all 10/100 ports to operate at line-rate

- Flow-based central rate limiting that can be applied to any classified packet flow
- 255 port based and MAC based VLANs
- 16,384 MAC addresses
- 4 hardware queues per 10/100 port; 8 hardware queues per 10/100/1000 port
- 4 10/100/1000BASE-T copper ports and 4 SFP GBIC ports deliver four active gigabit uplinks for greater throughput and four redundant uplinks for high availability
- ACLs for optimal security and diverse traffic classification

Summit 300-24

- Non-blocking wire-speed architecture
- 11.8 Gbps switching fabric, enabling all 10/100 ports to operate at line-rate
- Flow-based central rate limiting that can be applied to any classified packet flow
- 255 port based and MAC based VLANs
- 8,191 MAC addresses
- 4 hardware queues per port
- 4 Gigabit Ethernet uplink ports, 2 active and 2 redundant with Layer 1 failover
- ACLs for optimal security and diverse traffic classification
- ExtremeWare Intelligent Services

ExtremeWare Intelligent Services

Security

- DoS protection
- Intelligent Network Access with integration with EPICenter Policy Manager, including compatibility with Sygate host integrity checking
- IP Address Security: DHCP Option 82
- IP Address Security: Disable ARP learning
- Layer 2/3/4 Access Control points
- MAC Address Security (lockdown + limit)
- Management Security: SNMPv3, SSH2-client, SCP/SFTP
- Multiple supplicants
- Network Login
 - 802.1x
 - Web-based Network Login
- RADIUS authentication separated between Network Access and Device Management Security
- SSH2 server
- TACACS+ support

Technical Specifications

Availability

- ESRP (in Advanced Edge license)
- Ethernet Automatic Protection Switching-edge
- Loop detection via Lbdetect and ELRP CLI
- Network Address Translation
- RSTP: 802.1w Rapid Spanning Tree
- Software Redundant Port
- STP: Compatibility mode for PVST+, EMISTP (1 domain per port)
- VRRP (in Advanced Edge license)
- LACP for edge deployment (server connectivity)

QoS

- 4 priority queues
- 802.1p priority marking
- Layer 2 classification
- Layer 3 DiffServ
- Layer 2/3/4 ACLs

Routing

- ESRP, VRRP
- OSPF Edge
- RIP v1/v2

Multicast—Edge

- IGMP v1/v2
- IGMP snooping
- PIM/SM edge
- Multicast: static IGMP membership
- Static multicast routes
- Simplicity
- Entity MIB for inventory
- mtrace/mrinfo

Management Features

- Serial management port on the front panel for ease of installation
- Extensive management through SNMP, RMON and command line interface
- More secure remote management with strong encryption using SSH2
- Port mirroring

ExtremeWare 7.7 Supported Protocols

General Routing and Switching

- RFC 1812 Requirements for IP Version 4 Routers
- RFC 1519 CIDR
- RFC 1256 IPv4 ICMP Router Discovery (IRDP)
- RFC 1122 Host Requirements
- RFC 768 UDP
- RFC 791 IP
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 894 IP over Ethernet
- RFC 1027 Proxy ARP
- RFC 2338 VRRP
- RFC 3619 Ethernet Automatic Protection Switching (EAPS) and EAPsv2
- IEEE 802.1D – 1998 Spanning Tree Protocol (STP)
- IEEE 802.1w – 2001 Rapid Reconfiguration for STP, RSTP
- IEEE 802.1s – 2004 Multiple Instances of STP, MSTP
- Extreme Multiple Instances of Spanning Tree Protocol (EMISTP)
- PVST+, per VLAN STP (802.1Q interoperable)
- Extreme Standby Router Protocol (ESRP)
- IEEE 802.1Q – 2003 Virtual Bridged Local Area Networks
- Extreme Discovery Protocol (EDP)
- Static Unicast Routes
- Extreme Loop Recovery Protocol (ELRP)
- Software Redundant Ports

VLANs

- IEEE 802.1Q VLAN Tagging
- IEEE 802.3ad Static configuration and dynamic (LACP) for server attached
- IEEE 802.1v: VLAN classification by Protocol and Port
- Port-based VLANs
- MAC-based VLANs
- Multiple STP domains per VLAN

Quality of Service and Policies

- IEEE 802.1D – 1998 (802.1p) Packet Priority
- RFC 2474 DiffServ Precedence, including 4 queues/port
- RFC 2598 DiffServ Expedited Forwarding (EF)
- RFC 2597 DiffServ Assured Forwarding (AF)
- RFC 2475 DiffServ Core and Edge Router Functions
- Ingress Rate Limiting
- Layer 1-4, Layer 7 (user name) Policy-Based Mapping
- Policy-Based Mapping/Overwriting of DiffServ code points, .1p priority
- Network Login/802.1x and DLCS (Dynamic Link Context System, WINS snooping) based integration with EPICenter Policy Manager for dynamic user/device based policies

RIP

- RFC 1058 RIP v1
- RFC 2453 RIP v2

OSPF

- RFC 2328 OSPF v2 (including MD5 authentication)
- RFC 1587 OSPF NSSA Option
- RFC 1765 OSPF Database Overflow
- RFC 2370 OSPF Opaque LSA Option

Note: OSPF Edge License includes 2 active

interfaces, router priority 0

IP Multicast

- RFC 2362 PIM-SM
- RFC 1112 IGMP v1
- RFC 2236 IGMP v2
- IGMP Snooping with Configurable Router Registration Forwarding
- IGMP Filters
- Static IGMP Membership
- Static Multicast Routes
- Mtrace, draft-ietf-idmr-traceroute-ipm-07
- Mrinfo

Management and Traffic Analysis

- RFC 2030 SNMP, Simple Network Time Protocol v4
- RFC 1866 HTML – web-based device management and Network Login
- RFC 2068 HTTP server
- RFC 854 Telnet client and server
- RFC 783 TFTP Protocol (revision 2)
- RFC 951, 1542 BootP
- RFC 2131 BOOTP/DHCP relay agent and DHCP server
- RFC 1591 DNS (client operation)
- RFC 1155 Structure of Mgmt Information (SMIv1)
- RFC 1157 SNMPv1
- RFC 1212, RFC 1213, RFC 1215 MIB-II, Ethernet-Like MIB & TRAPS
- RFC 1573 Evolution of Interface
- RFC 1901 – 1908 SNMP Version 2c, SMIv2 and Revised MIB-II
- RFC 2570 – 2575 SNMPv3, user based security, encryption and authentication
- RFC 2576 Coexistence between SNMP Version 1, Version 2 and Version 3
- RFC 2665 Ethernet-Like-MIB
- RFC 1757 RMON 4 groups: Stats, History, Alarms and Events
- RFC 2021 RMON2 (probe configuration)
- RFC 2668 802.3 MAU MIB
- RFC 1643 Ethernet MIB
- RFC 1493 Bridge MIB
- RFC 2737 Entity MIB, Version 2
- RFC 2674 802.1p/802.1Q MIBs
- RFC 1354 IPv4 Forwarding Table MIB
- RFC 2233 Interface MIB
- RFC 2096 IP Forwarding Table MIB
- RFC 1724 RIPv2 MIB
- RFC 1850 OSPFv2 MIB
- RFC 2787 VRRP MIB
- RFC 2925 Ping/Traceroute/NSLOOKUP MIB
- RFC 2932 – IPv4 Multicast Routing MIB
- RFC 2933 – Internet Group Management Protocol MIB
- RFC 2934 – Protocol Independent Multicast MIB for IPv4
- Draft-ietf-bridge-rstpmib-03.txt – Definitions of Managed Objects for Bridges with Rapid Spanning Tree Protocol
- draft-ietf-bridge-8021x-01.txt (IEEE8021-PAE-MIB)
- IEEE 802.1x – 2001 MIB
- Extreme extensions to 802.1x-MIB
- Secure Shell (SSHv2) clients and servers
- Secure Copy (SCPv2) client and server
- Secure FTP (SFTP) server
- Configuration logging
- Multiple Images, Multiple Configs
- BSD System Logging Protocol (SYSLOG), with Multiple Syslog Servers
- Local Messages (criticals stored across reboots)
- IEEE 802.1ab Link Layer Discovery Protocol (LLDP)

Technical Specifications

ExtremeWare vendor MIBs: includes ACL, MAC FDB, IP FDB, MAC Address Security, Software Redundant Port, NetFlow, DoS-Protect MIB, QoS policy, Cable Diagnostics, VLAN config, vMAN, VLAN Translation and VLAN Aggregation MIBs

Security

- Routing protocol MD5 authentication (see above)
- Secure Shell (SSHv2), Secure Copy (SCPv2) and SFTP with encryption/authentication
- SNMPv3 user based security, with encryption/authentication (see above)
- RFC 1492 TACACS+
- RFC 2865 RADIUS Authentication
- RFC 2866 RADIUS Accounting
- RFC 3579 RADIUS Support for Extensible Authentication Protocol (EAP)
- RFC 3580 802.1X RADIUS
- RADIUS Per-command Authentication
- MAC based Network Login using RADIUS
- Access Profiles on All Routing Protocols
- Access Profiles on All Management Methods
- Network Login (web-based DHCP/HTTP/RADIUS mechanism)
- RFC 2246 TLS 1.0 + SSL v2/v3 encryption for web-based Network Login
- IEEE 802.1x – 2001 Port-Based Network Access Control for Network Login
- Multiple supplicants for Network Login (web-based and 802.1x modes)
- Guest VLAN for 802.1x
- MAC Address Security – Lockdown, limit and aging
- IP Address Security with DHCP Option 82, DHCP Enforce/Duplicate IP Protection via ARP Learning Disable
- Network Address Translation (NAT)
- Layer 2/3/4/7 ACLs
- Source IP Lockdown – Dynamic filtering against invalidly sourced traffic

Denial of Service Protection

- RFC 2267 Network Ingress Filtering
- RPF (Unicast Reverse Path Forwarding) Control via ACLs
- Wire-speed ACLs
- Rate limiting ACLs
- IP Broadcast Forwarding Control
- ICMP and IP-Option Response Control
- SYN attack protection
- FDB table resource protection via IPDA Subnet Lookup
- CPU DOS protection with ACL integration: Identifies packet floods to CPU and sets an ACL automatically, configurable enhanced DoS Protect
- Unidirectional Session Control

Robust Against Common Network Attacks

- CERT (<http://www.cert.org>)
 - CA-2003-04: “SQL Slammer”
 - CA-2002-36: “SSHredder”
 - CA-2002-03: SNMP vulnerabilities
 - CA-98-13: tcp-denial-of-service
 - CA-98.01: smurf
 - CA-97.28: Teardrop_Land -Teardrop and “LAND” attack
 - CA-96.26: ping
 - CA-96.21: tcp_syn_flooding
 - CA-96.01: UDP_service_denial
 - CA-95.01: IP_Spoofing_Attacks_and_Hijacked_Terminal_Connections
 - IP Options Attack

Host Attacks

- Teardrop, boink, opentear, jolt2, newtear, nestea, syndrop, smurf, fraggle, papasmurf, synk4, raped, winfreeze, ping -f, ping of death, pepsi5, Latierra, Winnuke, Sipping, Sping, Ascend, Stream, Land, Octopus

Summit 300-48 General Specifications

Switch Fabric

- Bandwidth: non-blocking, 32 Gbps

Forwarding Rate

- 13.1 million packets/second
- Max Packet Size: 1,522

Ports

- 48 RJ-45 10/100 ports (IEEE 802.3 Type 10BASE-T; 802.3u Type 100BASE-TX)
- 8 dual personality ports (four active max.). Four RJ-45 10/100/1000 ports (IEEE 802.3 Type 10BASE-T; 802.3u Type 100BASE-TX; 802.3ab 1000BASE-T Gigabit Ethernet) and 4 open SFP GBIC slots

General

- Number of QoS queues/port: 4 per 10/100 port
- Number of VLANs: 255VLAN Types: Port, IEEE 802.1Q, and MAC-based
- Number of ACL Rules/lines: 1014 (can be applied to either ingress or egress)

Forwarding Tables

- Layer 2/MAC Addresses: 8K
- Layer 3 forwarding database in hardware: 2K
- Layer 3 Routing table size: 8K

Rate Limiting

- Flow-based Bandwidth policing/rate limiting: pool of 315 rate limiters that can be applied to any classified ACL flow (ingress flows)
- Rate Limiting Granularity: 1Mb/s on 10/100BASE-T ports. 8Mb/s on 1000BASE-T ports

Physical Specifications

Dimensions

- (H) 3.5 in x (W) 17.25 in (D) x 18.25 in
- (H) 8.9 cm (W) 43.87 cm x (D) 46.41 cm
- Weight: 14 lbs (6.35 Kg) (1 PSU)
- PSU Weight: 2.2 lbs (1.0 Kg)

Operating Specifications

- Operating Temperature 0° C to 40° C (32 F to 104 F)
- Storage Temperature: -40° C to 70° C (-40 F to 158 F)
- Operating Humidity: 10% to 95% relative humidity, non-condensing
- Operational Shock: 30 m/s² (3g)

Acoustics

- Sound Power in accordance with EN 300 753
- Sound Power = 62 dBA per ISO 7779
- Declared Sound Power = 6.5 belsA per ISO 7779 & ISO 9296

Sound Pressure in accordance with NEBS

GR-63 Core

- Bystander Sound Pressure = 54 dBA right side @ .6m per NEBS GR-63

Power

AC Voltage Input Range	90-240 VAC
Input Amperage	3.2A @ 200VAC () 6.8A @ 90VAC ()
AC Line Frequency	47 to 63 Hz
Heat Dissipation:	631 BTU/hr (185 watts)

Power Over Ethernet

Summit 300-48 supports 802.3af PoE power management

- Available PoE power with the one power supply shipped with the system is 450 Watts
- Available PoE power with additional hot-swappable redundant power supply (p/n 15412) is 480 Watts

Regulatory/Safety

North American Safety of ITE

- UL 60950 3rd Edition, Listed Device (U.S.)
- CSA 22.2#60950-00 (Canada)
- Complies with FCC 21CFR1040.10 & 1040.11, LN#50 7/2001 (U.S. Laser Safety)
- CDRH Letter of Approval (U.S. FDA Approval)
- NOM/NYCE (Mexico)

European Safety of ITE

- EN60950:2000
- EN 60825-1+A2:2001 (Lasers Safety)
- 73/23/EEC Low Voltage Directive

International Safety of ITE

- CB Scheme IEC 60950:1999+All Country Deviations
- AS/NZX 3260 (Australia /New Zealand)
- GOST (Russia)

EMI/EMC:

North America EMC for ITE

- FCC CFR 47 part 15 Class A (U.S.A.)
- ICES-003 Class A (Canada)

European EMC standards

- EN 55022:1998 Class A
- EN 55024:1998 Class A includes IEC 61000-4-2, 3, 4, 5, 6, 8, 11
- EN 61000-3-2,3 (Harmonics & Flicker)
- ETSI EN 300 386:2001 (EMC Telecommunications)
- 89/336/EEC EMC Directive

International EMC Certifications

- CISPR 22:1997 Class A (International Emissions)
- CISPR 24:1997 Class A (International Immunity)
- IEC/EN 61000-4-2 Electrostatic Discharge
- IEC/EN 61000-4-3 Radiated Immunity
- IEC/EN 61000-4-4 Transient Burst
- IEC/EN 61000-4-5 Surge
- IEC/EN 61000-4-6 Conducted Immunity
- IEC/EN 61000-4-11 Power Dips & Interruptions

Country Specific

- VCCI Class A (Japan Emissions)
- AS/NZS 3548 ACA (Australia Emissions)
- NOM/NYCE (Mexico)
- CNS 13438:1997 Class A (BSMI-Taiwan)
- MIC Mark, EMC Approval (Korea)
- GOST (Russian Federation)

Environmental

- EN/ETSI 300 019-2-1 v2.1.2 – Class 1.2 Storage
- EN/ETSI 300 019-2-2 v2.1.2 – Class 2.3 Transportation
- EN/ETSI 300 019-2-3 v2.1.2 – Class 3.1e Operational
- EN/ETSI 300 753 (1997-10) – Acoustic Noise
- ASTM D3580 Random Vibration Packaged 1.5G

Reliability

- Calculated MTBF: 124,768 hours
- Fan Redundancy, resilient to up to 2 fan failures

Warranty

- 12-months Limited on Hardware
- 90-days on Software

Technical Specifications

Summit 300-24 General Specifications

Switch Fabric

- Bandwidth: nonblocking, 11.8 Gbps

Forwarding Rate

- 6.55 million packets/second
- Max Packet Size: 1,522

Ports

- 24 RJ-45 10/100 ports (IEEE 802.3 Type 10BASE-T; 802.3u Type 100BASE-TX)
- 2 dual personality ports: Either RJ-45 10/100/1000 ports (IEEE 802.3 Type 10BASE-T; 802.3u Type 100BASE-TX; 802.3ab-1000BASE-T Gigabit Ethernet) or open mini-GBIC slot

General

- Number of QoS queues/port: 4
- Number of VLANs: 255
- VLAN Types: Port, IEEE 802.1Q, and MAC-based
- Number of ACL Rules/lines: 1014 (can be applied to either ingress or egress)

Forwarding Tables

- Layer 2/MAC Addresses: 8K
- Layer 3 forwarding database in hardware: 2K
- Layer 3 Routing table size: 8K

Rate Limiting

- Flow-based Bandwidth policing/rate limiting: pool of 315 rate limiters that can be applied to any classified ACL flow (ingress flows)
- Rate Limiting Granularity: 1Mb/s on 10/100BASE-T ports. 8Mb/s on 1000BASE-T ports

Physical Specifications

Dimensions

- Height: 1.75 Inches/4.4 Cm
- Width: 17.35 Inches/44.1 Cm
- Depth: 15.3 Inches/37.5 Cm
- Weight: 14 lbs/6.4Kg

Operating Specifications

- Operating Temperature Range: 0° to 40° C (32° to 104° F)
- Storage Temperature Range: -40° to +70° C (-40° to 158° F)
- Humidity Range: 10-95% (RH) non-condensing
- Acoustic:
 - 43.6 dBA Sound Pressure per ISO 7779 clause 8
 - 5.2 belsA Sound Power per ISO 7779 clause 7 in accordance with
 - EN 300 753 as specified in EN/ETSI 300 019
- EN 300 753 (1997-10) – Acoustic Noise - Operational
- ASTM D3332 * – Shock – Unpackaged
- ASTM D3580 * – Random Vibration – Unpackaged

Power

- The Summit 300-24 supports 802.3af PoE power management
- Power requirements with no PoE devices connected to the ports:
 - Min Voltage/Associated Current: 100VAC/0.60A
 - Max Voltage/Associated Current: 240VAC/0.25A
 - Heat Dissipation, Watts: 60 W/198 BTU/hr
 - Total AC power consumption: 60 W

- Power requirements with a total of 370 watts of PoE delivered to the ports
- Min Voltage/Associated Current: 100VAC/5.5A
 - Max Voltage/Associated Current: 240VAC/2.3A
 - Heat Dissipation, Watts: 144 W/490 BTU/hr
 - Total AC power consumption: 510 W

Regulatory/Safety

Safety

- North America
 - cULus Listed device – UL 60950:2000 (US Safety)
 - CAN/CSA-C22.2 No. 60950-00 (Canadian Safety)
- Europe
 - Low Voltage Directive (LVD)
 - TUV-R GS Mark by German Notified Body
 - EN60950:2000 (European Safety)
- International
 - CB Scheme – IEC60950:2000 with all country deviations
 - (International Safety)
 - Country Specific
 - Mexico NOM/NYCE (Product Safety & EMC Approval)
 - Australia/New Zealand AS/NZS 3260 (ACA DoC, Safety of ITE)
 - Argentina S-Mark
 - GOST (Russia)

Laser Safety

- North America
 - FCC 21 CFR1040.10 & 1040.11 (Safety of Laser Products)
 - CDRH Letter of Approval (U.S. FDA Approval)
- Europe
 - EN60825-2 (European Safety of Lasers)

EMI/EMC

North America

- FCC 47 CFR Part 15 Class A (U.S. Emissions)
- ICES-003 Class A (Canada Emissions)

Europe 89/336/EEC EMC Directive

- ETSI/EN 300 386:2001 (EU Telecommunication Emissions & Immunity)
- EN55022:1998 Class A (Europe Emissions)
- EN55024:1998 includes IEC/EN 61000-2,3,4,5,6,11 (Europe Immunity)
- EN 61000-3-2, -3 (Europe Harmonics and Flicker)

International

- IEC/CISPR 22:1997 Class A (International Emissions)
- IEC/CISPR 24:1998 (International Immunity)
- IEC/EN 61000-4-2 Electrostatic Discharge
- IEC/EN 61000-4-3 Radiated Immunity
- IEC/EN 61000-4-4 Transient Bursts
- IEC/EN 61000-4-5 Surge
- IEC/EN 61000-4-6 Conducted Immunity
- IEC/EN 61000-4-11 Power Dips & Interruptions

Country Specific

- Japan Class A (VCCI Registration, Emissions)
- Australia/New Zealand AS/NZS 3548 (ACA DoC, Emissions)
- Korean MIC Mark (MIC Approval, Emissions & Immunity)
- Mexico NOM/NYCE (Product Safety & EMC Approval)
- GOST (Russia)
- Taiwan CNS 13438:1997 Class A (BSMI Approval, Emissions)

Environmental Standard

- EN 300 019-2-1 (2000-09) – Storage Class 1.2 Packaged
- EN 300 019-2-2 (1999-09) – Transportation Class 2.3 - Packaged
- EN 300 019-2-2 (1999-09) – Stationary Use at Weather Protected locations, Class 3.1e

Reliability

- Calculated MTBF: 142,333 hours

Warranty

- Limited Lifetime Warranty on Hardware
- 90-days on Software

Ordering Information

Part Number	Name	Description
15402	Summit 300-48	Layer 2/Layer 3/WLAN switch, 48 10/100BASE-TX PoE, 4 1000BASE-T & mini-GBIC based 1000BASE-X slots (unpopulated), Advanced Edge software, Wireless feature pack, single 600W AC power supply (450W available to PoE devices). Includes power cord for U.S. & Japan
15412	Summit 300-48 Spare 600W PSU	600W AC power supply (450W available to power Ethernet devices). Redundant and Load sharing power supply or spare
15441	Summit 300-48 Spare Blank Panel	Optional slot cover. For sparing only
13245	Summit 300-24	Summit 300-24, 24 10/100 ports w/Power over Ethernet, 2 1000BT, 2 mini-GBIC, Edge EW
13246	Voucher, Summit 300-24 Advanced Edge	Summit 300-24 Advanced Edge ExtremeWare Upgrade License. Includes wireless
45019	EPS-LD External AC PSU	External PoE Power System (Summit 300-24 cable included; Alpine FM-32Pi cable not included)
15700	Altitude 300-2i North America	802.11a/b/g, dual radio, integrated 2.4 & 5 GHz antennas, AES, 10/100BASE-TX PoE port; mounting accessories (U.S., Canada only)
15701	Altitude 300-2d North America	802.11a/b/g, dual radio, detachable RP-TNC (2.4 GHz) & RP-SMA (5 GHz) antenna connectors, AES, 10/100BASE-TX PoE port; mounting accessories (U.S., Canada only)
15702	Altitude 300-2i Japan	802.11a/b/g, dual radio, integrated 2.4 & 5 GHz antennas, AES, 10/100BASE-TX PoE port; mounting accessories; meets regulatory certification for Japan
15703	Altitude 300-2d Japan	802.11a/b/g, dual radio, detachable RP-TNC (2.4 GHz) & RP-SMA (5 GHz) antenna connectors, AES, 10/100BASE-TX PoE port; mounting accessories; meets regulatory certification for Japan
15706	Altitude 300-2i EU and RoW	802.11a/b/g, dual radio, integrated 2.4 & 5 GHz antennas, AES, 10/100BASE-TX PoE port; mounting accessories; meets regulatory certification for EU and all other countries excluding NA, Japan & Taiwan
15707	Altitude 300-2d EU and RoW	802.11a/b/g, dual radio, detachable RP-TNC (2.4 GHz) & RP-SMA (5 GHz) antenna connectors, AES, 10/100BASE-TX PoE port; mounting accessories; meets regulatory certification for EU and all other countries excluding NA, Japan & Taiwan
15901	Indoor/Outdoor Dual Band Dir. Ant.	Indoor/outdoor integrated dual band 2.4 GHz & 5 GHz diverse directional antenna. Includes indoor mounting and 1m/3 foot cable. Use with 15701, 15703, or 15707 Access Points
15902	Antenna Outdoor Mounting Kit	Outdoor mounting kit for 15901 detachable antenna. Includes universal mounting bracket for wall, ceiling and pool installations, nuts, bolts and fasteners
10051	SX mini-GBIC	Mini-GBIC, SFP, 1000BASE-SX, LC Connector
10052	LX mini-GBIC	Mini-GBIC, SFP, 1000BASE-LX, LC connector
10053	ZX mini-GBIC	Mini-GBIC, SFP, Extra long distance SMF 70 Km/21 dB budget, LC connector



www.extremenetworks.com

email: info@extremenetworks.com

Corporate and North America
 Extreme Networks, Inc.
 3585 Monroe Street
 Santa Clara, CA 95051 USA
 Phone +1 408 579 2800

Europe, Middle East, Africa and South America
 Phone +31 30 800 5100

Asia Pacific
 Phone +852 2517 1123

Japan
 Phone +81 3 5842 4011

© 2006 Extreme Networks, Inc. All rights reserved.

Extreme Networks, the Extreme Networks Logo, Access Adapt, Alpine, BlackDiamond, EPICenter, Extreme Standby Routing Protocol, ExtremeWare, Summit, and Unified Access Architecture, are either registered trademarks or trademarks of Extreme Networks, Inc. in the United States and/or other countries.

Specifications are subject to change without notice.

1028_06 11/06

Summit 300 Series Data Sheet