

IBM *@server*® xSeries 336



Highlights

- ***New dual-core Intel® Xeon™ Processors deliver outstanding performance over a wide range of applications***
- ***Integrated system management processor and optional Remote Supervisor II SlimLine simplify administration with flexible levels of control***
- ***New high-availability features help improve system and application uptime***

Performance optimized for 32- and 64-bit environments

The IBM *@server*® xSeries® 336 offers superb performance for demanding Web and collaborative applications. Support for dual-core Intel Xeon Processors helps provide investment protection, better levels of performance and reliability. Intel Extended Memory 64 Technology provides outstanding performance by allowing operating systems and applications to physically address more memory. To take advantage of this, the x336 supports eight DIMM slots for a maximum of 16GB of DDR II memory.

Enjoy improved manageability

The x336 offers advanced features that help simplify systems management. An integrated service processor and optional Remote Service Adapter II SlimLine offer complete, in-band local and remote management capabilities. IBM Director software provides an easy-to-use interface to manage groups of systems together.

Take advantage of greater ease of use

Advanced usability features on the x336 include new, optional hot-swap redundant power supplies to help reduce unplanned downtime. Hot-swap and redundant fans keep components cool and enable easy fan replacement without taking the server offline. In the event of a problem, a drop-down light path diagnostics panel enables administrators to troubleshoot often without opening the server. And Remote Deployment Manager helps simplify server installation by allowing you to remotely deploy hundreds of servers from a single console.

Get it now

go to **ibm.com/eserver/xseries** or call 1 888 **ShopIBM**

to buy direct or to locate an IBM reseller

Select configurations of the x336 are part of the IBM Express Portfolio™, designed, developed and priced to meet the specific needs of mid-sized businesses. The IBM Express Portfolio of solutions is easy to acquire, install and manage. Express models and configurations vary by country.

© Copyright IBM Corporation 2005

Produced in the USA

November 2005

All Rights Reserved

xSeries 336 at a glance

Form factor/height	Rack/1U
Processor (max)	Intel Xeon Processor up to 3.80 GHz/800 MHz front-side bus and Dual-Core Intel Xeon Processor 2.8 GHz
Number of processors (std/max)	1/2
Cache (max)	Up to 2MB L2 per processor core
Memory ¹ (max)	512MB or 1GB/16GB PC2-3200 DDR II
Expansion slots	1 PCI-X (64-bit 100 MHz) and 1 PCI-X (64-bit 133 MHz) or 1 PCI-Express x8
Disk bays (total/hot-swap)	2/2 or 4/4
Maximum internal storage ^{1,2}	600GB Ultra320 SCSI or 500GB simple-swap SATA
Network interface	Integrated dual Gigabit Ethernet
Power supply (std/max)	585W 1/2
Hot-swap components	Power supply, fans, hard disk drives (select models)
RAID support	Integrated RAID-1, -1E, optional RAID-5
Systems management	Integrated Service Processor, Diagnostic LEDs, drop-down light path diagnostics panel, Automatic Server Restart, Alert Standard Format 2.0, optional Remote Supervisor Adapter II SlimLine, IBM Director, ServerGuide™ and optional Remote Deployment Manager
Operating systems supported	Microsoft® Windows® Server™ 2003, Windows 2000 Server/Advanced Server, Red Hat® Enterprise Linux® 3.0, SUSE LINUX Enterprise Server 8.0 and 9.0, TurboLinux Enterprise Server 8.0, Novell NetWare 6.5 and VMware™ ESX Server™ v2.5
Limited warranty ³	3-year onsite limited warranty

For more information

World Wide Web

U.S.

ibm.com/eserver/xseries

Canada

ibm.com/ca/eserver/xseries

¹ Maximum internal hard disk and memory capacities may require the replacement of any standard hard drives and/or memory and the population of all hard disk bays and memory slots with the largest capacity supported drives available. When referring to variable speed CD-ROMs, CD-Rs, CD-RWs and DVDs, actual playback speed will vary and is often less than the maximum possible.

² GB and TB = 1,000,000,000 and 1,000,000,000,000 bytes, respectively, when referring to storage capacity. Accessible capacity is less.

³ Visit **ibm.com/pc/safecomputing** periodically for the latest information on safe and effective computing.

Warranty Information: For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC 27709, Attn: Dept. JDJA/B203. IBM makes no representation or warranty regarding third-party products or services, including those designated as ServerProven® or ClusterProven®.

Telephone support may be subject to additional charges. For onsite labor, IBM will attempt to diagnose the problem remotely before sending a technician.

IBM reserves the right to change specifications or other product information without prior notice. This publication could include technical inaccuracies or typographical errors. References herein to IBM products or services do not imply that IBM intends to make them available in other countries. IBM PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OR CONDITION OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore, this statement may not apply to you.

This publication was produced in the United States. IBM may not offer the products, services or features discussed in this document in other countries, and the information may be subject to change without notice. Consult your local IBM business contact for information on the product or services available in your area.

All statements regarding IBM's future direction and intent are subject to change or withdrawal without notice, and represent goals and objectives only.

Information about non-IBM products is obtained from the manufacturers of those products or their published announcements. IBM has not tested those products and cannot confirm the performance, compatibility, or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

IBM, the IBM logo, the e-business logo, @server, ClusterProven, Express Portfolio, Predictive Failure Analysis, ServerGuide, ServerProven, ServeRAID and xSeries are trademarks or registered trademarks of IBM Corporation in the United States, other countries or both. For a list of additional trademarks, go to **ibm.com/legal/copytrade.shtml**.

Intel, Intel Xeon, Intel Inside and the Intel Inside logo are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Microsoft, Windows, Windows Server and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.

Red Hat is a registered trademark of Red Hat, Inc., in the United States and other countries.

Linux is a trademark of Linus Torvalds in the United States, other countries, or both.

Other company, product and service names may be trademarks or service marks of others.

XSD00361-USEN-04