



# ADSL2/2+ MINI-PIM

## Product Overview

The ADSL2/2+ Mini-Physical Interface Modules (Mini-PIMs) are for use with the Juniper Networks SSG20 Secure Services Gateway. The ADSL2/2+ Mini-PIMs, one supporting Annex A over plain old telephone service (POTS) and the other Annex B over ISDN, each include one physical asymmetric digital subscriber line (ADSL) port that supports ADSL, ADSL2, or ADSL2+ protocols.

## Product Description

The Juniper Networks® single-port ADSL2/2+ Mini-PIMs for the Juniper Networks SSG20 Secure Services Gateway can be used to provide ADSL WAN connectivity. The ADSL2/2+ Annex A (over POTS) and ADSL2/2+ Annex B (over ISDN) support ADSL, ADSL2, and ADSL2+ protocols.

## Features and Benefits:

- Automatic configuration of ADSL line after negotiating with the digital subscriber line access multiplexer (DSLAM), minimizing configuration
- One RJ-11 or RJ-45 ADSL interface
- Supports ADSL, ADSL2, and ADSL2+ protocols on the same interface card
- Dying Gasp support
- Multilink Point-to-Point Protocol (MLPPP) over two ADSL cards
- Supports ATM Adaption Layer 5 (AAL5) with constant bit rate (CBR), variable bit rate nonreal time (VBR-NRT), and unspecified bit rate (UBR) traffic types

**Table 1: ADSL/ADSL2/ADSL2+ Features and Benefits**

FEATURE	FEATURE DESCRIPTION	BENEFIT
ADSL/ADSL2/ADSL2+ support	Same module can be used in ADSL, ADSL2, and ADSL2+ environments	Provides investment protection when upgrading WAN connectivity
Automatic configuration	Automatically configures the ADSL line after negotiating with the DSL access multiplexer (DSLAM)	Minimizes configuration and support overhead
Dedicated network processor	Provides additional processing resources	Helps maintain predictable WAN performance by offloading the J Series or SSG Series CPU
Dying gasp support	Notifies the DSLAM, in the event of power loss, that the SSG Series or J Series is about to go offline	Reduces downtime associated with unplanned power outages



1-Port ADSL 2/2+ Mini-PIM with Annex A (Over POTS)



1-Port ADSL 2/2+ Mini-PIM with Annex B (Over ISDN)

## Specifications

### Dimensions (W x H x D) and Weight

- 3.75 x 0.8 x 5.9 in (9.5 x 2 x 14.5 cm)
- 0.17 lb (77.1 g)

### ATM

- ATM Adaptation Layer 5 (AAL5)
- Up to 10 permanent virtual connections (PVCs) per card
- CBR, VBR-NRT, and UBR

### Environmental

- Operating temperature: 0 to 40°C
- Storage temperature: -40 to 70° C
- Relative humidity: 5 to 90% noncondensing

### Diagnostics

- Operation, Administration, and Maintenance (OAM) F4 far loopback test
- OAM F4 near loopback test
- OAM F5 far loopback test
- OAM F5 near loopback test

### LEDs

PIM LEDs indicate port status with the following LED states:

- SYNC – Green
- TX/RX – Green

### Management Capabilities

- Telnet/Console/Web: Remote and local configuration, monitoring, and troubleshooting

### Standards and Compliance

#### Safety

- CAN/CSA-C22.2 No. 60950-1-03/UL 60950-1 Third Edition, Safety of Information Technology Equipment
- EN 60950-1:2001+A11, Safety of Information Technology Equipment
- IEC 60950-1:2001 First Edition, Safety of Information Technology Equipment

### EMC (Emissions)

- AS/NZS CISPR22 Class B
- EN-61000-3-2 Harmonic current emissions
- EN-61000-3-3 Voltage fluctuations
- FCC Part 15 Class B (USA)
- EN 55022 Class B (Europe)
- VCCI Class B (Japan)
- BSMI Class B (Taiwan)

### Immunity

- EN 55024
- EN-61000-4-2 ESD
- EN-61000-4-3 Radiated Immunity
- EN-61000-4-4 EFT
- EN-61000-4-5 Surge
- EN-61000-4-6 Low Frequency Common Immunity
- EN-61000-4-11 Voltage Dips and Sags

### European Telecommunications Standardization Institute (ETSI)

- ETSI EN-300386-2: Telecommunication Network Equipment Electromagnetic Compatibility Requirements

### Telecom

- FCC Part 68/TIA-968
- IC CS-03

### Standards

- ANSI T1.413 II compliant (vendor version 1)
- G994.1 (G.HS) Version 05/03 + Amendment 1 (02/04)
  - Annex A (POTS overlay)
  - Annex B (ISDN overlay)
  - Appendix 1 (ATM Interface – Utopia)
- G992.1 (G.DMT; ADSL)
  - Annex A (POTS Overlay)
  - Annex B (ISDN Overlay)
  - Appendix 1 (ATM Interface-Utopia)
- G992.3 (G.DMTbis; ADSL2) + Amendment 1,2
  - Annex A (POTS overlay)

## Specifications (continued)

### Standards (continued)

- Annex B (ISDN overlay)
  - Annex L (Reach Extended)
  - Appendix 1 (ATM Interface – Utopia)
- G992.5 (ADSL2+) + Corrigendum 1 + Amendment 2
  - Annex A (POTS overlay)
  - Annex B (ISDN overlay)
  - Appendix 1 (ATM Interface – Utopia)
- ETSI TS 101 388 V1.3.1

### Performance-Enabling Services and Support

Juniper Networks is the leader in performance-enabling services and support, which are designed to accelerate, extend, and optimize your high-performance network. Our services allow you to bring revenue-generating capabilities online faster so you can realize bigger productivity gains, faster rollouts of new business models and ventures, and greater market reach, while generating higher levels of customer satisfaction. At the same time, Juniper Networks ensures operational excellence by optimizing your network to maintain required levels of performance, reliability, and availability. For more details, please visit [www.juniper.net/products-services](http://www.juniper.net/products-services).

## Ordering Information

PRODUCT NUMBER	DESCRIPTION
JXM-1ADSL2-A-S	1-port ADSL 2/2+ interface card with Annex A (over POTS) support, RJ-11
JXM-1ADSL2-B-S	1-port ADSL 2/2+ interface card with Annex B (over ISDN) support, RJ-45

### ScreenOS Software Release

ADSL2/2+ Annex A and Annex B functionality is supported in ScreenOS 5.4 or greater.

### About Juniper Networks

Juniper Networks, Inc. is the leader in high-performance networking. Juniper offers a high-performance network infrastructure that creates a responsive and trusted environment for accelerating the deployment of services and applications over a single network. This fuels high-performance businesses. Additional information can be found at [www.juniper.net](http://www.juniper.net).

---

**Corporate And Sales Headquarters**

Juniper Networks, Inc.  
1194 North Mathilda Avenue  
Sunnyvale, CA 94089 USA  
Phone: 888.JUNIPER (888.586.4737)  
or 408.745.2000  
Fax: 408.745.2100

**APAC Headquarters**

Juniper Networks (Hong Kong)  
26/F, Cityplaza One  
1111 King's Road  
Taikoo Shing, Hong Kong  
Phone: 852.2332.3636  
Fax: 852.2574.7803

**EMEA Headquarters**

Juniper Networks Ireland  
Airsides Business Park  
Swords, County Dublin, Ireland  
Phone: 35.31.8903.600  
Fax: 35.31.8903.601

Copyright 2009 Juniper Networks, Inc. All rights reserved. Juniper Networks, the Juniper Networks logo, JUNOS, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. "Engineered for the network ahead" and JUNOSe are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered marks, or registered service marks are the property of their respective owners. Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

To purchase Juniper Networks solutions, please contact your Juniper Networks representative at 1-866-298-6428 or authorized reseller.

