



OCTAL E&M

ATLAS 550 EXPANSION MODULE

PRODUCT FEATURES

- Eight voice ports operate in 2-wire or 4-wire Type I, II, III, IV, and V signaling modes
- Trunk interfaces to PBX or key system
- Supports transmission only mode for leased line modem applications
- Supports press-to-talk applications using Type V signaling
- Accepts all ATLAS 550 resource modules
- Flash upgradeable

The ATLAS 550 Octal E&M module provides eight ports for 2-wire and 4-wire E&M applications for PBXs, key systems, and leased line analog modems. E&M signaling types I, II, III, IV, and V are supported, as well as a Transmission Only (TO) mode. Type V signaling can be utilized for press-to-talk applications. The module is intended for on-premise applications and therefore makes no provision for sealing current. Signaling originates on the E-lead.

The Octal E&M module can be used in ATLAS 550 applications utilizing dedicated, ISDN, T1, and Frame Relay circuits. Each port provides an RJ-45 interface and can be independently configured. The module installs in any of the four user interface module slots in the ATLAS 550 and is flash upgradeable.

CORPORATE OFFICE

ADTRAN, Inc.
901 Explorer Boulevard
P.O. Box 140000
Huntsville, AL 35814-4000

800 9ADTRAN
256 963-8000
fax: 256 963-8699
fax back: 256 963-8200
e-mail: info@adtran.com
web site: www.adtran.com

REGIONAL OFFICES

Chicago, IL 800 436-4217
Seattle, WA 800 390-1573
Washington, DC 800 794-9798

FIELD OFFICES

Atlanta, GA 800 289-0966
Chicago, IL 800 471-8655
Columbus, OH 888 865-2237
Dallas, TX 800 471-8648
Denver, CO 800 471-8651
Irvine, CA 800 788-5408
Kansas City, KS 800 471-8649
Los Angeles, CA 888 223-7668
Nashville, TN 888 223-7657
New York, NY 800 471-8657
Portland, OR 888 223-7660
Richmond, VA 800 689-9915
San Jose, CA 888 223-7655

INTERNATIONAL CONTACTS

Asia Pacific/Australia
852-2824-8283 (Hong Kong)
Canada
800 232-6811
Caribbean/Latin America
954 746-5355
All other International inquiries
256 963-2500



I.S. EN ISO 9001

ADTRAN is an ISO 9001
registered company.



Printed in the U.S.A. on recycled paper.
61200313L1-8A August 2000
©2000 ADTRAN, Inc. All rights reserved.

Product Specifications

PHYSICAL INTERFACE

- Modular RJ-45

OPERATING MODES

- 4-Wire E&M
- 2-Wire E&M
- 4-Wire Transmission Only (No signaling)
- 2-Wire Transmission Only (No signaling)

IMPEDANCE

- 4W Impedance: 600 Ω
- 2W Impedance: 600 Ω +2.15 μ F

FREQUENCY RESPONSE

- 300-3400 hz (+/-1.0dB)

TLP LEVELS

- TX: -12dB~ +6dB gain, 3dB steps (+12dB~ -6dB TLP)
- RX: 12dB~ +6dB gain, 3dB steps (-12dB~ +6dB TLP)

SIGNALING MODES

- E-Lead originate
- Types I, II, III, IV, V

ENVIRONMENT

- Operating Temperature: 0° to 50°C, (32° to 122°F)
- Storage Temperature: -20° to 70°C, (-4° to 158°F)
- Relative Humidity: Up to 95%, non-condensing

PHYSICAL

- Module Dimensions: 7.0" W, 10.0" D, 1.25" H
- Weight: 1.51 lbs

AGENCY APPROVALS

- FCC Part 15 (A), CISPR 22 (A), Industry Canada CS03, UL 1950, CUL IEC 950

PRODUCT INCLUDES


- User manual

Ordering Information

EQUIPMENT

PART

Octal E&M Module1200313L1



Specifications subject to change without notice.