Product data sheet

Specifications



Discontinued

Rack PDU, Metered, Zero U, 14.4kW,208V,(24)C13,(4)C19, (2)L6-30R, 10' Cord

AP7899

Discontinued on: Dec 16, 2020

End-of-service on: Nov 9, 2022

Main

Main Input Voltage	208 V 3 phase
Output voltage	208 V
PDU Type	Metered
Number of rack unit	0U
Number of cables	1
Cable length	10 ft (3.05 m)
Provided Equipment	Cord retention bracket(s) Documentation CD Installation guide Rack Mounting brackets RS-232 configuration cable Toolless Mounting Kit
Input Frequency	50/60 Hz
Line Rated Current	40 A
Input current limits	50 A
Load Capacity	14400 VA
Number of input connectors	1 CS8365
Max current draw	40 A
Number of power socket outlets	2 NEMA L6-30R 24 IEC 60320 C13 4 IEC 60320 C19
Protection Type	Circuit breaker

Complementary

Color	Black
Height	70.0 in (177.8 cm)
Width	2.2 in (5.6 cm)
Depth	3.7 in (9.5 cm)
Net Weight	22.84 lb(US) (10.36 kg)
Mounting Location	Side
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Vertical

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environmental

Product Certifications	cUL Listed CSA Industry Canada METI Denan UL Listed
Standards	FCC Part 15 class A ICES-003 UL 60950
Ambient Air Temperature for Operation	23…113 °F (-5…45 °C)
Relative Humidity	5…95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13…149 °F (-25…65 °C)
Storage Relative Humidity	5…95 %
Storage altitude	0…50000 ft (0…15240 m)

Ordering and shipping details

GTIN	731304240730

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	81.0 in (205.7 cm)
Package 1 Width	3.1 in (7.9 cm)
Package 1 Length	12.2 in (31.1 cm)
Package weight(Lbs)	31.57 lb(US) (14.32 kg)

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

EU RoHS Directive	Compliant By Exemption

Energy efficiency

Optimized Energy Efficiency	Energy efficient product

Use Again

Repack and remanufacture

Take-back	Yes

Image of product / Alternate images

Alternative




















B3
B2
B1