

AP7840

★★★★★ (0) [Write a review](#)

Metered rack Power Distribution Units (PDUs) provide real-time remote monitoring of connected loads. User-defined alarms warn of potential circuit overloads before ...

Includes: Installation Guide, Rack Mounting Brackets, Toolless Mounting Kit, User Manual



Technical Specifications

Output

Nominal Output Voltage	200V, 208V
Overload Protection	No
Maximum Total Current Draw	20
Output Connections	(4) IEC 320 C19 (Battery Backup) (20) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	200V, 208V, 230V
Input frequency	50/60 Hz
Input Connections	NEMA L6-20P
Cord Length	10ft (3.05meters)
Number of Power Cords	1
Load Capacity	3328VA
Maximum Input Current	20A
Regulatory Derated Input Current (North America)	16A

Physical

Maximum Height	63.75inches (1619MM, 161.9CM)
Maximum Width	2.19inches (56MM, 5.6CM)
Maximum Depth	1.73inches (44MM, 4.4CM)
Net Weight	10.0lbs. (4.55KG)
Shipping weight	17.0lbs. (7.73KG)
Shipping Height	84.0inches (2134MM, 213.4CM)
Shipping Width	6.0inches (152MM, 15.2CM)
Shipping Depth	5.0inches (127MM, 12.7CM)
Color	Black

Environmental

Operating Temperature	32 - 113 °F (0 - 45 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-50000ft (0-15000meters)

Conformance

Approvals	cUL Listed, CSA C22.2 No. 60950-1-03, FCC Part 15 Class A, ICES-003, Industry Canada, PSE, UL 60950-1, UL Listed, VCCI Class A
Standard warranty	2 years repair or replace

Sustainable Offer Status

PEP	Available in Documentation tab
EOLI	Available in Documentation tab

