

- [Home](#)
- [Products](#)
- [Support](#)
 - [Search the Knowledge Base](#)
 - [Ask APC](#)
 - [My Support](#)
- [Services](#)
- [Selectors](#)
 - [UPS Selector](#)
 - [InfraStruXure Estimator](#)
 - [Wiring Closet And Server Room Selector](#)
 - [UPS Upgrade Selector](#)
 - [Surge Protection Selector](#)
 - [Rack Configurator](#)
 - [Service Selector](#)
- [How to Buy](#)
 - [Try out the APC Product Selectors](#)
 - [Online Reseller Listing](#)
 - [Locate a Reseller/Partner](#)

[Home](#) >> [Products](#) >> [Power Distribution](#) >> [Switched Rack PDU](#)

[Switched Rack PDU](#)

Rack PDU, Switched, Zero U, 20A, 120V, (24)5-20



APC Switched Rack PDU , Input: 100V, 120V , Input Connections: NEMA L5-20P , Cord Length: 10 feet (3.05 meters) , Output: 120V , Output Connections: NEMA 5-20R

Includes: Cord retention bracket(s), Installation guide, Rack Mounting brackets, Toolless Mounting Kit, User Manual

[+ More Images](#)

Standard Lead Time: Usually in Stock


AP7930

 [Email Technical Specifications](#)


 [Printer Friendly](#)

- [Technical Specifications](#)
- [Product Overview](#)
- [Documentation](#)
- [Software & Firmware](#)
- [Options](#)
- [Compare Models](#)

Output

| | | |
|--------------------------------------|-----------------|---|
| Nominal Output Voltage | 120V | |
| Maximum Total Current Draw per Phase | 20A | |
| Output Connections | (24) NEMA 5-20R |  |
| Always on Outlets | 24 | |
| Overload Protection | No | |

Input

| | | |
|--|-------------|---|
| Nominal Input Voltage | 100V,120V | |
| Input Frequency | 50/60 Hz | |
| Regulatory Derated Input Current (North America) | 16A | |
| Input Connections | NEMA L5-20P |  |
| Cord Length | 3.05 meters | |
| Number of Power Cords | 1 | |
| Acceptable Input Voltage | 100-120 VAC | |
| Maximum Input Current per phase | 20A | |
| Load Capacity | 1920 VA | |

Physical

| | |
|-----------------|------------|
| Net Weight | 5.91 KG |
| Maximum Height | 1619.00 mm |
| Maximum Width | 56.00 mm |
| Maximum Depth | 44.00 mm |
| Shipping Weight | 6.82 KG |
| Shipping Height | 2134.00 mm |

| | |
|----------------|-----------|
| Shipping Width | 152.00 mm |
| Shipping Depth | 127.00 mm |
| Color | Black |

Environmental

| | |
|-----------------------------|----------------|
| Operating Environment | -5 - 45 °C |
| Operating Relative Humidity | 5 - 95% |
| Operating Elevation | 0-3000 meters |
| Storage Temperature | -25 - 65 °C |
| Storage Relative Humidity | 5 - 95% |
| Storage Elevation | 0-15000 meters |

Conformance

| | |
|----------------------|--|
| Regulatory Approvals | cUL Listed,CSA,FCC Part 15 Class A,ICES-003,Industry Canada,UL 60950,UL Listed |
| Standard Warranty | 2 years repair or replace |

[Copyright](#) © American Power Conversion Corp., all rights reserved