

- [Home](#)
- [Products](#)
- [Support](#)
  - [Search the Knowledge Base](#)
  - [Ask APC](#)
  - [My Support](#)
- [Services](#)
- [Selectors](#)
  - [UPS Selector](#)
  - [InfraStruXure Estimator](#)
  - [Wiring Closet And Server Room Selector](#)
  - [UPS Upgrade Selector](#)
  - [Surge Protection Selector](#)
  - [Rack Configurator](#)
  - [Service Selector](#)
- [How to Buy](#)
  - [Try out the APC Product Selectors](#)
  - [Online Reseller Listing](#)
  - [Locate a Reseller/Partner](#)

[Home](#) >> [Products](#) >> [Power Distribution](#) >> [Switched Rack PDU](#)

## **Switched Rack PDU**

### **Rack PDU, Switched, Zero U,12.5kW,208V, (21)C13&(3)C19; 3' Cord**

AP7968

 [Email Technical Specifications](#)

 [Printer Friendly](#)



APC Switched Rack PDU , Input: 208V  
3PH , Input Connections: CS8365 , Cord  
Length: 3 feet ( 0.91 meters ) ,  
Output: 208V , Output Connections: IEC  
320 C13,IEC 320 C19



**Includes:** Cord retention bracket(s),  
Documentation CD, Installation guide, Rack  
Mounting brackets, RS-232 configuration  
cable, Toolless Mounting Kit

[+ More Images](#)

**Standard Lead Time:** Usually in Stock

- [Technical Specifications](#)
- [Product Overview](#)
- [Documentation](#)
- [Software & Firmware](#)
- [Options](#)
- [Compare Models](#)

#### Output

Nominal Output Voltage	208V	
Maximum Total Current Draw per Phase	35A	
Output Connections	(21) IEC 320 C13	
	(3) IEC 320 C19	
Overload Protection	Yes	

#### Input

Nominal Input Voltage	208V 3PH
Input Frequency	50/60 Hz
Input Connections	CS8365
Cord Length	0.91 meters
Number of Power Cords	1
Maximum Line Current per phase	35A
Maximum Input Current per phase	35A
Load Capacity	12.5 kVA

#### Physical

Net Weight	8.08 KG
Maximum Height	1778.00 mm
Maximum Width	56.00 mm
Maximum Depth	89.00 mm
Shipping Weight	11.04 KG

Shipping Height	2108.00 mm
Shipping Width	152.00 mm
Shipping Depth	127.00 mm
Color	Black

**Environmental**

Operating Environment	-5 - 45 °C
Operating Relative Humidity	5 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95%
Storage Elevation	0-15000 meters

**Conformance**

Regulatory Approvals	cUL Listed,CSA,FCC Part 15 Class A,ICES-003,Industry Canada,UL 60950,UL Listed
Standard Warranty	2 years repair or replace
Environmental Compliance	RoHS 7b Exemption