

Brocade Ethernet Optics Family

HIGHLIGHTS

- Rigorously tested for performance and reliability by Brocade
- Hot-swappable flexibility in the field for greater ease and lower total cost of ownership
- Standards-based—802.3z, 802.3ah, 802.3u, 802.3ae, 802.3ak, and 802.3ba—and compliant as required
- Compliant with Restrictions on Hazardous Substances (RoHS), meeting either RoHS 5 or RoHS 6 EU standards

Highly Reliable, Brocade-Qualified Optics

Brocade offers a unique set of high-performance, reliable, and cost-effective optical transceivers to help enterprises and service providers meet the challenges of diverse network topologies. To ensure maximum quality, Brocade selects and tests the most reliable, highest-performing optical transceivers on the market, and then warrants their availability, capacity, and performance in Brocade[®] products.

Extensive performance and reliability testing reflects an ongoing commitment to quality. Brocade tests transceivers using the industry's most advanced tools and instruments to help ensure that they provide the right mix of functionality and performance when used in conjunction with Brocade products. The speed, capacity, reliability, and low cost of ownership that Brocade is known for is also provided in all optical components.

By using Brocade-qualified components, organizations can be assured that their warranty and service requirements will be met and that their Brocade products will continually provide the uptime, performance, and reliability required by today's leading enterprise service providers.

Ethernet Optics Family Features

The Brocade Ethernet optics family includes several offerings designed to meet the performance and scalability requirements of service provider and enterprise environments. The new 100 Gigabit Ethernet (GbE) CFP optics deliver even greater performance capacity to support cloud services for these environments.

100 MbE Optics

- 100 Megabit Ethernet (MbE) transceivers support link lengths from 2 km to 40 km
- Both SMF and MMF fiber types
- RoHS 5 and 6 compliant
- Enterprise switching and routing

1 GbE Optics

- 1 GbE transceivers support link lengths from 300 m to 100 km
- Both SMF and MMF fiber types
- Coarse Wavelength Division Multiplexing (CWDM) support for distances of 80 km to 100 km
- RoHS 5 and 6 compliant
- For core routers and security applications

10 GbE Optics

- 10 GbE transceivers support link lengths of 26 m to 80 km
- Protocol-independent
- Less than one-third the power and size of MSA optic
- Hot-swappable
- Digital Optical Monitoring (DOM) support
- RoHS 5 and 6 compliant
- Application delivery and acceleration
- High-Performance Computing (HPC) interconnects
- Service provider traffic management

POS Pluggable OC12, OC48, and OC192 XFP Optics

- Pluggable XFP optic
- Ranges from 500 m to 80 km

40 GbE QSFP+ Optics

- 40 GbE transceivers support link lengths up to 100 m
- Hot-pluggable
- Industry-standard QSFP+
- Digital Optical Monitoring (DOM) support
- High-density 40 GbE connectivity options for data center, enterprise, and service provider applications

100 GbE CFP Optics

- 100 GbE transceivers support link lengths up to 40 km
- Hot-pluggable
- Low voltage
- Industry-standard CFP
- Diagnostic features per CFP MSA for laser bias, temperature, supply voltage
- Carrier, service provider, and cloud services
- Enterprise campus core routing
- RoHS 6 compliant

Brocade Global Services

Brocade Global Services has the expertise to help organizations build scalable, efficient cloud infrastructures. Leveraging 20 years of expertise in storage, networking, and virtualization, Brocade Global Services delivers world-class professional services, technical support, network monitoring services, and education, enabling organizations to maximize their Brocade investments, accelerate new technology deployments, and optimize the performance of networking infrastructures.

Affordable Acquisition Options

Brocade Capital Solutions helps organizations easily address their IT requirements by offering flexible network acquisition and support alternatives. Organizations can select from purchase, lease, Brocade Network Subscription, and Brocade Subscription Plus options to align network acquisition with their unique capital requirements and risk profiles. To learn more, visit www.Brocade.com/CapitalSolutions.

Maximizing Investments

To help optimize technology investments, Brocade and its partners offer complete solutions that include professional services, technical support, and education. For more information, contact a Brocade sales partner or visit www.brocade.com.

Product Support for Fast Ethernet

Fast Ethernet Optics	Brocade ICX® Switches			FastIron® Series		FastIron X Series	BigIron® Series	NetIron® Series		
	ICX 6430/6450	ICX 7450	ICX 6610	LS/WS/GS	FCX	SX	RX	XMR/MLX*	CES/CER/CER-RT	Brocade 6910
EIMG-100FX-OM	•	•	• ¹	•	•	• ²	•	•	•	•
EIMG-100FX-IR-OM		•	• ¹	•	•	• ²	•	•	•	•
EIMG-100FX-LR-OM		•	• ¹	•	•	• ²	•	•	•	•

¹ Available only with Brocade ICX 6610-24F.

² Available only with SX-FI424HF and SX-FI-24HF.

Product Support for 1 Gigabit Ethernet

1 GbE Fiber Optics	Brocade ICX Switches							FastIron Series		FastIron X Series	BigIron Series	NetIron Series			ServerIron® Series	TurboIron®	Brocade VDX® Switches
	ICX 6430	ICX 6450	ICX 7250	ICX 7450	ICX 6610	ICX 6650	ICX 7750	WS	FCX	SX	RX	XMR/MLX	CES/CER/CER-RT	Brocade 6910	ADX*	24X	VDX 6710/6720/6730/6740/8770
EIMG-SX-OM	⊙ ¹	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
EIMG-SX-OM-T														•			
EIMG-LX-OM	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
EIMG-LX-OM-T														•			
EIMG-LHA-OM	•	•			•			•	•	• ³	•	•	•	•		•	
EIMG-LHA-OM-T			•	•			•							•			
EIMG-LHB	•	•			•			•		• ³	•	•	•	•			
EIMG-BXD	•	•	•	•	•		•		•	•	•	•	•	•		•	
EIMG-BXU	•	•	•	•	•		•		•	•	•	•	•	•		•	
EIMG-CWDM80-XXXX					•			•		•	•	•	•	•			
EIMG-TX	⊙ ¹	•	•	•	•	•	•	•	• ²	•	•	•	• ⁵		•	•	
XBR-000190												• ⁴					•
1G-SFP-C-0x01	⊙ ¹	•	•														

⊙ Optics supported for both stacking and regular data links. For further details, visit www.brocade.com/fastironstacking.

¹ Stacking is not supported on the Brocade ICX 6430 12-port compact switch.

² Only qualified on FCX-624S-F.

³ Not qualified on SX-FI-24HF.

⁴ Qualified on Brocade MLX 24x1 GbE-X, Brocade MLX 10 GbE×4 SFP+, Brocade MLX 10 GbE×20 SFP+ modules.

⁵ Qualified for 10/100/1000 Mbps speed.

Product Support for 10 Gigabit Ethernet

	Brocade ICX Switches						FastIron Series	FastIron X Series	BigIron Series	NetIron Series		ServerIron Series	Turbolron	Brocade VDX Switches
	ICX 6450	ICX 7250	ICX 7450	ICX 6610	ICX 6650	ICX 7750				XMR/MLX	CER/CES/CER-RT			
10 GbE Fiber Optics							FCX	SX	RX	XMR/MLX	CER/CES/CER-RT	ADX	24X	VDX 6710/6720/6730/6740/8770
10G-XFP-SR, LR							•	• ³	• ⁵	• ⁵	•	•		
10G-XFP-ER							•	• ³	• ⁵	• ⁵	•			
10G-XFP-ZR							•	• ³	• ⁵	• ⁵	•			
10G-XFP-1310-LRM							•							
10G-SFPP-USR	⊙ ¹	⊙	⊙	•	•	•	⊙	• ⁴		•	•		•	•
10G-SFPP-SR	⊙ ¹	⊙	⊙	•	•	•	⊙	• ⁴	•	• ⁵	•	• ⁷	•	•
10G-SFPP-LR	•	⊙	⊙	•	•	•	•	• ⁴	•	• ⁵	•	• ⁷	•	•
10G-SFPP-ER	•	•	•	•	•	•	•	• ⁴	•	• ⁵	•		•	•
10G-SFPP-ZR		•	•			•				•	•			
10G-SFPP-ZRD-T										• ⁶				
10G-SFPP-LRM	⊙ ¹		•	•			⊙ ²	• ⁴		•	• ⁷	•	•	
10G-SFPP-TWX-XXXX	•	⊙	⊙	⊙	•	•	⊙	• ⁴		•	•		•	•
10G-SFPP-AOC-XXXX		•	•		•	•				•	•			•

⊙ Optics supported for both stacking and regular data links. For further details, visit www.brocade.com/fastironstacking.

¹ Stacking is not supported on the Brocade ICX 6450 12-port compact switch.

² Available only with the FCX-2SFPP module.

³ SX-FI42XGW module supports WAN mode.

⁴ Available only with SX-FI-8XG, SX-FI-2XG, SX-FI-2XGMR-XL, and SX-FI-2XGMR-XL-PREM6 modules.

⁵ The Brocade MLX and NetIron XMR modules (BR-MLX-10Gx8-X, BR-MLX-10Gx8-M, BR-MLX-10Gx4-X, BR-MLX-10Gx4-X-ML, NI-MLX-10Gx4, NI-MLX-10Gx2, NI-XMR-10Gx4, NI-XMR-10Gx2) and the Brocade BigIron RX 10 GbE modules support WAN mode.

⁶ Available only with the Brocade MLXe 8x10 GbE and 24x10 GbE modules.

⁷ Available only with Brocade ADX 1000F.

Product Support for 40 Gigabit Ethernet

	Brocade ICX Switches ¹				Brocade VDX Switches	Brocade MLX Series
	ICX 7450	ICX 6610	ICX 7750	ICX 6650	VDX 6740/6940/8770	MLXe
40 GbE Fiber Optics						
40G-QSFP-SR4	⊙		⊙	•	•	•
40G-QSFP-SR4-INT			•	•	•	
40G-QSFP-ESR4			•		•	
40G-QSFP-LR4	•		⊙	•	•	•
40G-QSFP-LM4	•		•			
40G-QSFP-4SFP-C-XXXX			•	•		
40G-QSFP-QSFP-C-XXXX	⊙		⊙	•		
40G-QSFP -C-XXXXX	⊙	⊙ ¹	⊙			
40G-QSFP-QSFP-AOC-XXXX	⊙		⊙			

⊙ Optics supported for both stacking and regular data links. For further details, visit www.brocade.com/fastironstacking.

¹ 40 GbE ports on the Brocade ICX 6610 are supported for stacking only.

Product Support for 100 Gigabit Ethernet

	Brocade MLX Series	Brocade VDX Switches
100 GbE Fiber Optics	MLXe	VDX 8770
100G-CFP- SR10	•	
100G-CFP-10X10-2KM-OM	•	
100G-CFP-10X10-10KM-OM	•	
100G-CFP-LR4-10KM	•	
100G-CFP-ER4-40KM	•	
100G-CFP2-LR4-10KM	•	•
100G-CFP2-SR10	•	•

Key Standards and Features

	IEEE Standards	Domestic Safety Standards	International Safety Standards	Wavelength (nm)	Fiber Type	Maximum Cable Distance	Digital Optical Monitoring
Fast Ethernet							
EIMG-100FX-OM	802.3u	FDA 21CFR 1040.10 Class 1,	EN 60825-1, EN 60950-1	1,310	MMF	2 km	Yes
EIMG-100FX-IR-OM	802.3	CSA 60950-1-03/UL		1,310	SMF	15 km	Yes
EIMG-100FX-LR-OM	802.3	60950-1		1,310	SMF	40 km	Yes
1 GbE Fiber							
EIMG-SX-OM/ EIMG-SX-OM-T	802.3z	FDA 21CFR 1040.10 Class 1, CSA 60950-1-03/UL 60950-1	EN 60825-1, EN 60950-1	850	MMF	220 m to 550 m	Yes
EIMG-LX-OM/ EIMG-LX-OM-T	802.3z			1,310	MMF/SMF	550 m to 10 km	Yes
EIMG-LHA-OM/ EIMG-LHA-OM-T	802.3z			1,550	SMF	70 km	Yes
EIMG-LHB	802.3z			1,550		150 km w/0.18 dB/km cable, 91 km w/standard 0.3 dB/km cable	No
EIMG-BXD	802.3ah			TX: 1,490 RX: 1,310		10 km	No
EIMG-BXU	802.3ah			TX: 1,310 RX: 1,490		10 km	No
EIMG-CWDM80-XXXX	802.3z			1,470 to 1,610		80 km	No
1000BASE-T Copper							
EIMG-TX, XBR-000190	802.3z	CSA 60950-1-03/UL	EN 60950-1	N/A	Cat5	100 m	N/A
1G-SFP-TWX-0x01	802.3z	Direct-attached SFP copper cables				1 m, 5 m	No
10 GbE Fiber							
10G-XFP-SR	802.3ae	FDA 21CFR 1040.10 Class 1, CSA 60950-1-03/UL 60950-1	EN 60825-1, EN 60950-1	850	MMF	26 m to 300 m	Yes
10G-XFP-LR	802.3ae			1,310	SMF	10 km	
10G-XFP-ER	802.3ae			1,550		40 km	
10G-XFP-ZR	802.3ae			1,550		80 km	
10G-XFP-1310-LRM	802.3aq			1,310		220 m	
10G-SFPP-USR	N/A			850	MMF	100 m	
10G-SFPP-SR	802.3ae			850	MMF	26 m to 300 m	
10G-SFPP-LR	802.3ae			1,310	SMF	10 km	
10G-SFPP-ER	802.3ae			1,550	SMF	40 km	
10G-SFPP-ZR	802.3ae			1,550	SMF	80 km	
10G-SFPP-ZRD-T	802.3-2005 Clause 52 standard			102 C-band tunable wavelengths from 1,528 to 1,568 (50 GHz apart)	SMF	80 km	
10G-SFPP-LRM	802.3ae			1,310	MMF	220 m	

Key Standards and Features (Continued)

	IEEE Standards	Domestic Safety Standards	International Safety Standards	Wavelength (nm)	Fiber Type	Maximum Cable Distance	Digital Optical Monitoring
10GBASE Cable							
10G-SFP-TWX-XXXX	802.3ae	Direct-attached SFP+ Twinax copper cables				1 m, 3 m, 5 m	No
10G-SFP-AOC-XXXX	N/A	Direct-attached SFP+ active optical cables				7 m, 10 m	No
40 GbE Fiber							
40G-QSFP-SR4	802.3ba	FDA 21CFR 1040.10 Class 1, CSA 60950-1-03/UL 60950-1	EN 60825-1, EN 60950-1	850	OM3 MMF	100 m	Yes
					OM4 MMF	150 m	
40G-QSFP-SR4-INT (compatible with 10GBASE-SR)	802.3ba				OM3 MMF	100 m	Yes
		OM4 MMF	150 m				
40G-QSFP-LR4	802.3ba			1,264.5 to 1,337.5	SMF	10 km	
40 GbE Copper							
40G-QSFP-4SFP-C-XXXX	N/A	Direct-attached QSFP+ to 4 SFP+ copper cables				1 m, 3 m, 5 m	No
40G-QSFP-QSFP-C-XXXX	N/A	Direct-attached QSFP+ to QSFP+ copper cables				1 m, 3 m, 5 m	No
100 GbE CFP Fiber							
100G-CFP-SR10	802.3ba	FDA 21CFR 1040.10 Class 1, CSA 60950-1-03/UL 60950-1	EN 60825-1, EN 60950-1	850	OM3 MMF	100 m	Yes
					OM4 MMF	150 m	
100G-CFP-LR4-10KM	802.3ba			1,294.53 to 1,310.19	SMF	10 km	Yes
100G-CFP-10x10-2KM-OM	10x10 MSA			1,523 to 1,595	SMF	2 km	Yes
100G-CFP-10x10-10KM-OM	10x10 MSA			1,523 to 1,595	SMF	10 km	Yes
100G-CFP-ER4-40KM	802.3ba	1,294.53 to 1,310.19	SMF	40 km	Yes		
100 GbE CFP2 Fiber							
100G-CFP2-LR4-10KM	IEEE 802.3ba			1,294.53 to 1,310.19	SMF	10 km	Yes
100G-CFP2-SR10	IEEE 802.3ba	UL/CSA 60950, CDRH Class 1	EN 60950, EN 60825 Class 1	840 to 860	OM3 MMF OM4 MMF	100 m 150 m	Yes

Brocade Ethernet Optics Ordering Information

Part Number	Description
100 MbE SFP Transceivers	
EIMG-100FX-OM	100BASE-FX SFP optic MMF, LC connector, optical monitoring capable.
EIMG-100FX-IR-OM	100BASEFX-IR SFP optic for SMF with LC connector, optical monitoring capable. For distances up to 15 km.
EIMG-100FX-LR-OM	100BASEFX-LR SFP optic for SMF with LC connector, optical monitoring capable. For distances up to 40 km.
1 GbE SFP	
EIMG-BXD	1000BASE-BXD SFP optic, SMF, 1,490 nm, LC connector. This optic can be connected only to an EIMG-BXU at the far end.
EIMG-BXU	1000BASE-BXU SFP optic, SMF, 1,310 nm, LC connector. This optic can be connected only to an EIMG-BXD at the far end.
EIMG-CWDM80-XXXX	CWDM SFP optic, 80 nm, 1,470 to 1,610 (total of eight wavelengths supplied by eight optics, each 20 nm apart in wavelength), LC connector.
EIMG-LHA-OM	1000BASE-LHA SFP optic SMF, LC connector, optical monitoring capable. For distances up to 70 km.
EIMG-LHA-OM-T	1000BASE-LHA SFP optic, MMF, LC connector, optical monitoring capable (70 km), industrial temperature.
EIMG-LHB	1000BASE-LHB SFP optic, SMF, LC connector, 150 km maximum reach.
EIMG-LX-OM	1000BASE-LX SFP optic SMF, LC connector, optical monitoring capable. For distances up to 10 km.
EIMG-LX-OM-T	1000BASE-LX SFP optic, SMF, LC connector, optical monitoring capable, industrial temperature.
EIMG-SX-OM	1000BASE-SX SFP optic, MMF, LC connector, optical monitoring capable.
EIMG-SX-OM-T	1000BASE-SX SFP optic, MMF, LC connector, optical monitoring capable, industrial temperature.
EIMG-TX, XBR-000190	1000BASE-T SFP copper, RJ-45 connector.
1G-SFP-C-0x01	1 GbE direct-attached SFP copper cable, 1 m or 5 m (where x=1 for 1 m; x=5 for 5 m).
10 GbE XFP	
10G-XFP-SR	850 nm serial pluggable XFP optic (LC), target range 300 m over MMF.
10G-XFP-LR	1310 nm serial pluggable XFP optic (LC) for up to 10 km over SMF.
10G-XFP-ER	1550 nm serial pluggable XFP optic (LC) for up to 40 km over SMF.
10G-XFP-ZR	1,550 nm serial pluggable XFP optic (LC) for up to 80 km over SMF.
10G-XFP-1310-LRM	10GBASE-LRM, XFP optic, 1,310 nm serial pluggable optic (LC) for use on OM1/OM2/OM3 MMF up to 220 m.

Brocade Ethernet Optics Ordering Information (Continued)

Part Number	Description
10 GbE SFP+	
10G-SFPP-USR	10 GbE Ultra-Short Reach (USR), SFP+ optic (LC), target range 100 m over MMF.
10G-SFPP-LR	10GBASE-LR, SFP+ optic (LC), for up to 10 km over SMF.
10G-SFPP-ER	10GBASE-ER, SFP+ optic (LC), for up to 40 km over SMF.
10G-SFPP-ZR	10GBASE-ZR, SFP+ optic (LC), for up to 80 km over SMF.
10G-SFPP-ZRD-T	10 GbE tunable DWDM SFP+ optic (LC), for up to 80 km over SMF.
10G-SFPP-LRM	10GBASE-LRM, SFP+ optic (LC), 220 m over OM1/OM2/OM3 MMF.
10G-SFPP-TWX-XXXX	10 GbE SFP+ direct-attached copper cable, 1 m, 3 m, or 5 m.
10G-SFPP-AOC-XXXX	10 GbE SFP+ direct-attached active optical cable, 7 m or 10 m.
40 GbE QSFP+	
40G-QSFP-SR4	40GBASE-SR4 QSFP+ optic (MTP 1×8 or 1×12), 100 m over MMF (not compliant with 10GBASE-SR4 modules per IEEE 802.ae standard).
40G-QSFP-ESR4	40GBASE-ESR4 QSFP+ optic (MTP 1×8 or 1×12), 300 m over MMF, (10GBASE-SR compatible, breakout)
40G-QSFP-SR4-INT	40GBASE-SR4 QSFP+ optic (MTP 1×8 or 1×12), 100 m over MMF (10GBASE-SR compatible, breakout-capable).
40G-QSFP-LR4	40GBASE-LR4 QSFP+ optic (LC), for up to 10 km over SMF.
40G-QSFP-4SFP-C-XXXX	4×10 GbE direct-attached QSFP+ to four SFP+ copper breakout cable, 1 m, 3 m, or 5 m.
40G-QSFP-QSFP-C-XXXX	4×10 GbE direct-attached QSFP+ to QSFP+ copper breakout cable, 1 m, 3 m, or 5 m.
100 GbE CFP	
100G-CFP-SR10	100 GbE CFP optic (MPO24), SR10, for distances up to 100 m over MMF
100G-CFP-LR4-10KM	100 GbE CFP optic (SC), LR4, for distances up to 10 km over SMF.
100G-CFP-10x10-2KM-OM	100 GbE CFP optic (LC), 10×10, for distances up to 2 km over SMF.
100G-CFP-10x10-10KM-OM	100 GbE CFP optic (LC), 10×10, for distances up to 10 km over SMF.
100G-CFP-ER4-40KM	100 GbE CFP optic (LC), ER4, for distances up to 40 km over SMF.
100 GbE CFP2	
100G-CFP2-SR10	100 GbE CFP2 optic, SR10, for distances up to 100 m over MMF, 1-pack.
100G-CFP2-LR4-10KM	100 GbE CFP2 optic (LC), LR4, for distances up to 10 km over SMF.

Corporate Headquarters

San Jose, CA USA
T: +1-408-333-8000
info@brocade.com

European Headquarters

Geneva, Switzerland
T: +41-22-799-56-40
emea-info@brocade.com

Asia Pacific Headquarters

Singapore
T: +65-6538-4700
apac-info@brocade.com



© 2015 Brocade Communications Systems, Inc. All Rights Reserved. 12/15 GA-DS-1344-16

ADX, Brocade, Brocade Assurance, the B-wing symbol, DCX, Fabric OS, HyperEdge, ICX, MLX, MyBrocade, OpenScript, The Effortless Network, VCS, VDX, Vplane, and Vyatta are registered trademarks, and Fabric Vision and vADX are trademarks of Brocade Communications Systems, Inc., in the United States and/or in other countries. Other brands, products, or service names mentioned may be trademarks of others.

Notice: This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment features, or service offered or to be offered by Brocade. Brocade reserves the right to make changes to this document at any time, without notice, and assumes no responsibility for its use. This information document describes features that may not be currently available. Contact a Brocade sales office for information on feature and product availability. Export of technical data contained in this document may require an export license from the United States government.

