


## SERIAL AND ASYNCHRONOUS HIGH-SPEED WAN INTERFACE CARDS FOR CISCO 1800, 2800, AND 3800 SERIES INTEGRATED SERVICES ROUTERS

Serial and asynchronous high-speed WAN interface cards (HWICs) provide highly flexible connections for Cisco® 1800, 2800, and 3800 series integrated services routers. These HWICs help customers to enable applications such as WAN aggregation, legacy protocol transport, console server, and dial access server. Customers can mix and match HWICs to tailor cost-effective solutions for common networking problems such as remote network management, external dial-modem access, low-density WAN aggregation, legacy protocol transport, and high port density support.

Cisco Systems® offers five serial and asynchronous HWICs:

1. Cisco 1800/2800/3800 series 4-Port Serial High-Speed WAN Interface Card (HWIC-4T)—Four high-speed serial ports ([Figure 1. A](#))
2. Cisco 1800/2800/3800 series 4-Port Asynchronous/Synchronous High-Speed WAN Interface Card (HWIC-4A/S)—Four low-speed synchronous/asynchronous ports ([Figure 1. B](#))
3. Cisco 1800/2800/3800 series 8-Port Asynchronous/Synchronous High-Speed WAN Interface Card (HWIC-8A/S-232)—Eight low-speed synchronous/asynchronous ports, EIA-232 only ([Figure 1. C](#))
4. Cisco 1800/2800/3800 series 8-Port Asynchronous High-Speed WAN Interface Card (HWIC-8A)—Eight asynchronous EIA-232 ports ([Figure 1. D](#))
5. Cisco 1800/2800/3800 series 16-Port Asynchronous High-Speed WAN Interface Card (HWIC-16A)—Sixteen asynchronous EIA-232 ports ([Figure 1. E](#))

**Figure 1.** Serial and Asynchronous HWICs




## COMMON APPLICATIONS

These highly flexible interface cards enable several important applications.

### WAN Aggregation

Serial interfaces can be used to aggregate WAN connection from remote sites. With support for serial speeds up to 8 Mbps per port, the 4-Port Serial High-Speed WAN Interface Card is ideal for low- and medium-density WAN aggregation ([Figure 2](#)).

**Figure 2.** WAN Concentration



### Legacy Protocol Transport

Serial and synchronous/asynchronous ports are ideally suited to transport legacy traffic across a TCP/IP network. This enables network convergence ([Figure 3](#)), eliminating costly separate leased lines for this traffic. Legacy protocols supported by Cisco IOS® Software include:

- Systems Network Architecture (SNA) and Synchronous Data Link Control (SDLC) Protocol
- Binary Synchronous Communications Protocol (Bisync)
- X.25 Protocol


**Figure 3.** Network Convergence



### Console and Terminal Server

Asynchronous ports provide highly flexible connections that allow access to EIA-232 devices across a TCP/IP network. This allows out-of-band management to console or craft ports, allowing the network operator to manage a network of remote devices from a central location (Figure 4).


Figure 4. Managing Multiple Remote Devices From a Single Location



### Dial Access Server

Asynchronous HWICs can connect to external dial modems to provide low-density dial access servers (Figure 5).

Figure 5. Dial Access Server



## CONNECTORS AND CABLING

Serial and asynchronous HWICs have connectors and cabling that allow high port densities in the compact HWIC form factor. Tables 1–4 show connector and cabling specifications.

**Table 1.** Connectors and Cabling

HWIC	Connectors	Available Cables
HWIC-4T, HWIC-4A/S	Smart Serial	See <a href="#">Table 2</a>
HWIC-8A/S-232	High-density 4-port connector	See <a href="#">Table 3</a>
HWIC-8A, HWIC-16A	High-density 8-port connector	High -density 8-port EIA-232 asynchronous cable (CAB-HD8-ASYNC) High-density 8-port asynchronous cable with eight DB-25 modem connectors (CAB-HD8-KIT)

### Smart Serial Cabling

The 4-Port Serial High-Speed WAN Interface Card and 4-Port Asynchronous/Synchronous High-Speed WAN Interface Card each have four Smart Serial ports. These ports use the same connectors and cabling as the WIC-2T and WIC-2A/S.

**Table 2.** Smart Serial Cabling for HWIC-4T and HWIC-4A/S

Product Number	Cable Type	Length	Connector Type
<b>CAB-SS-V35MT</b>	V.35 DTE	10 ft (3m)	Male
<b>CAB-SS-V35FC</b>	V.35 DCE	10 ft (3m)	Female
<b>CAB-SS-232MT</b>	EIA/TIA-232 DTE	10 ft (3m)	Male
<b>CAB-SS-232FC</b>	EIA/TIA-232 DCE	10 ft (3m)	Female
<b>CAB-SS-449MT</b>	EIA/TIA-449 DTE	10 ft (3m)	Male
<b>CAB-SS-449FC</b>	EIA/TIA-449 DCE	10 ft (3m)	Female
<b>CAB-SS-X21MT</b>	X.21 DTE	10 ft (3m)	Male
<b>CAB-SS-X21FC</b>	X.21 DCE	10 ft (3m)	Female
<b>CAB-SS-530MT</b>	EIA/TIA-530 DTE	10 ft (3m)	Male
<b>CAB-SS-530AMT</b>	EIA/TIA-530A DTE	10 ft (3m)	Male

### High-Density Synchronous/Asynchronous Cabling

The 8-Port Asynchronous/Synchronous High-Speed WAN Interface Card uses two high-density 4-port connectors. Each connector supports four ports of EIA-232 with data communications equipment (DCE) or data terminal equipment (DTE) interfaces. All four ports on one cable use the same DTE/DCE mode.

**Table 3.** High-Density Synchronous/Asynchronous Cabling

Product Number	Cable Type	Length	Connector Type
CAB-HD4-232FC	4-port EIA-232 DCE	10 ft (3m)	Female DB-25
CAB-HD4-232MT	4-port EIA-232 DTE	10 ft (3m)	Male DB-25

**High-Density Asynchronous Cabling**

The 8-Port Asynchronous High-Speed WAN Interface Card and 16-Port Asynchronous High-Speed WAN Interface Card use one (HWIC-8A) or two (HWIC-16A) high-density 8-port connectors. The 8-port asynchronous cable provides the high-density connector on one end and eight RJ-45 plugs on the other. RJ-45- to DB-25 modular adapters are used to convert the RJ-45 to DB-25 DTE or DB-25 DCE connections.

**Table 4.** High-Density Asynchronous Cabling

Product Number	Cable Type	Length	Connector Type
CAB-HD8-ASYNC	8-port EIA-232	10 ft (3m)	RJ-45
CAB-HD8-KIT	8-port EIA-232 plus eight CAB-25AS-MMOD	10 ft (3m)	Male DB-25
CAB-25AS-MMOD	RJ-45 to DB-25 adapter	–	Male DB-25
CAB-25AS-FDTE	RJ-45 to DB-25 adapter	–	Female DB-25

**PLATFORM SUPPORT**

Serial and asynchronous HWICs are supported in the HWIC slots of Cisco 1800, 2800, and 3800 series integrated services routers. [Table 5](#) indicates which platforms are supported. These HWICs are supported in all Cisco IOS Software feature sets. The minimum Cisco IOS Software is Release 12.3(14)T.

**Table 5.** Supported Platforms

HWIC Product Number	1841	2801	2811	2821	2851	3825	3845
HWIC-4T	No	Yes	Yes	Yes	Yes	Yes	Yes
HWIC-4A/S	Yes						
HWIC-8A/S-232	Yes						
HWIC-8A	Yes						
HWIC-16A	No	Yes	Yes	Yes	Yes	Yes	Yes

## SPECIFICATIONS

The specifications of the HWICs are listed in [Table 6](#).

**Table 6.** HWIC Specifications

Specification	HWIC-4T	HWIC-4A/S	HWIC-8A/S-232	HWIC-8A	HWIC-16A
<b>Synchronous Support</b>	Yes	Yes	Yes	No	No
<b>Synchronous Maximum Speed (per port)</b>	8 Mbps	256 kbps	256 kbps	N/A	N/A
<b>Asynchronous Support</b>	Yes	Yes	Yes	Yes	Yes
<b>Asynchronous Maximum Speed (per port)</b>	230.4 kbps	230.4 kbps	230.4 kbps	230.4 kbps	230.4 kbps
<b>Bisync Support</b>	Yes	Yes	Yes	No	No
<b>Serial Protocols</b>	EIA-232, EIA-449, EIA-530, EIA-530A, V.35, X.21	EIA-232, EIA-449, EIA-530, EIA-530A, V.35, X.21	EIA-232	EIA-232	EIA-232
<b>Lead Manipulation</b>	Yes	Yes	Yes	Yes	Yes
<b>Network Clock Synchronization</b>	Yes	Yes	Yes	No	No

### Common Specifications

The specifications listed below are common to all serial and asynchronous HWICs.

#### Agency Approvals

- UL 1950 (United States)
- CSA-C22.2 #950 (Canada)
- EN60950 (Europe)
- TUV GS (Germany)
- IEC 950 (International)

#### Immunity

- EN300386
- EN55024/CISPR24
- EN50082-1

#### Emissions

- FCC Part 15 Class A
- ICES-003 Class A
- EN55022 Class A
- CISPR22 Class A
- AS/NZS 3548 Class A
- VCCI Class A

- EN 300386
- EN61000-3-3
- EN61000-3-2

### Physical Specifications

- Single-wide HWIC, no slot restrictions
- Dimensions (H x W x D) 0.8 x 3.1 x 5.6 in. (2.1 x 7.9 x 14.2 cm)

### Environmental Specifications

- Operating temperature: 32 to 104°F (0 to 40°C)
- Storage temperature: -4 to 149°F (-20 to 65°C)
- Relative humidity: 10 to 90 percent, noncondensing



#### Corporate Headquarters

Cisco Systems, Inc.  
 170 West Tasman Drive  
 San Jose, CA 95134-1706  
 USA  
 www.cisco.com  
 Tel: 408 526-4000  
 800 553-NETS (6387)  
 Fax: 408 526-4100

#### European Headquarters

Cisco Systems International BV  
 Haarlerbergpark  
 Haarlerbergweg 13-19  
 1101 CH Amsterdam  
 The Netherlands  
 www-europe.cisco.com  
 Tel: 31 0 20 357 1000  
 Fax: 31 0 20 357 1100

#### Americas Headquarters

Cisco Systems, Inc.  
 170 West Tasman Drive  
 San Jose, CA 95134-1706  
 USA  
 www.cisco.com  
 Tel: 408 526-7660  
 Fax: 408 527-0883

#### Asia Pacific Headquarters

Cisco Systems, Inc.  
 168 Robinson Road  
 #28-01 Capital Tower  
 Singapore 068912  
 www.cisco.com  
 Tel: +65 6317 7777  
 Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Web site at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus • Czech Republic  
 Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland • Israel • Italy • Japan • Korea  
 Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland • Portugal • Puerto Rico • Romania • Russia  
 Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden • Switzerland • Taiwan • Thailand • Turkey • Ukraine  
 United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2005 Cisco Systems, Inc. All rights reserved. CCIP, CCSP, the Cisco *Powered Network* mark, Cisco Unity, Follow Me Browsing, FormShare, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, the Cisco IOS logo, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherSwitch, Fast Step, GigaStack, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MGX, MICA, the Networkers logo, Networking Academy, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, RateMUX, Registrar, ScriptShare, SlideCast, SMARTnet, StrataView Plus, Stratum, SwitchProbe, TeleRouter, The Fastest Way to Increase Your Internet Quotient, TransPath, and VCO are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Web site are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0501R) 204184.a\_ETMG\_CM\_1.05